

SNOWFLAKE G II SUF-65DG-C-

L

1-Door Freezer Cabinet, HC



PRODUKTSERIE: SNOWFLAKE GII
VARENUMMER: 877010824

The Snowflake GII series is brought to you by Japanese and Danish engineering excellence, dedicated to simplifying the day-to-day work routines of kitchen staffs all around the world.

The technology behind the performance boost of Snowflake GII is the tropicalised cooling system enduring up to +40°C. Additionally, the cooling agent of the new generation of Snowflake is the eco-friendly refrigerant R290, a natural gas (HC) that enhances the performance and cuts down energy consumption significantly.

Both interior and exterior are built of anti-corrosion stainless steel AISI 304, which is among the best choices for hygienic and food safe cooking environments.

The Snowflake GII SUF-65BG is a 1 door freezer cabinet with a net internal volume of 398 Ltr.

As a product that is designed and built to last, this freezer cabinet combines an innovative design concept, premium materials and clever extras:

- Minimum cool air lost: double insulated and extra wide door gaskets help to keep the cold air into the cabinet
- Both interior and exterior are built of stainless steel AISI 304, which is among the best choices for hygienic and food safe cooking environments
- Anti-tilt mechanism: moulded liners for saver container and rooster handling
- Reversible doors for maximum flexibility
- Removable gaskets make sure you can clean the device thoroughly
- This and other thoughtful extras, such as the cleaning-free condenser, are designed to reduce kitchen cleaning times whilst storing foods protectively in the best possible way

The refrigerant used in all Snowflake GII HC models is R290. This agent is a natural gas which enhances the performance of the refrigerated counter and has, compared to other refrigerants, a minimal ozone depletion potential.

UDVENDIG

Rustfrit stål AISI 304

INDVENDIG

Rustfrit stål AISI 304

Kølemiddeltype: R290

Energieffektivitetsklasse

D



HOSHIZAKI

SNOWFLAKE G II SUF-65DG-C-L

TEKNISKE SPECIFIKATIONER

Temperaturinterval	Hyldestørrelse	Volumen, brutto	Eltilslutning	Klimaklasse
-20/-10°C	2/1 GN Dyb	560 l	230V, 50Hz	5

FORSENDELSESSPECIFIKATIONER

Bruttovægt	Bredde	Dybde	Højde	Nettovægt
140 kg	654 mm	840 mm	1.996 mm	140 kg



Dimensionstegning følger inden længe



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige order@hoshizaki.se
Hoshizaki UK uksales@hoshizaki.uk
Eksportlande sales.ex@hoshizaki-europe.com
Øvrige lande sales.ex@hoshizaki-europe.com

www.hoshizaki.dk