Premier U 80 DR U Ru1

Refrigerator/Freezer 'U' type with RU1 valve for remote cooling system

PRODUKTSERIE: PREMIER W80
ARTIKELNUMMER: 188801031

2/1 GN

Hoshizaki Premier U 80 DR U Ru1 is a 2/1 GN wide cabinet with RU1 valve for connection to a remote cooling system. It is ready to install and is compatible with multiple refrigerants. This heavy duty cabinet has a gross volume of 700 ltr. and the height of the cabinet with adjustable legs is 2080-2130mm. Adjustable legs are 130-180mm. The depth is 728mm without pedal door opener (800mm incl. pedal door opener).

Ultimate flexibility with 'U' type cabinet:
The cabinet can be set to run as a refrigerator or as a freezer. Set the controller to run as either K, M or F cabinet with the following temperature ranges:
K: +2/+12°C M: -5/+12°C F: -25/-5°C

- Ready-to-install cabinet with RU1 valve
- Air circulation system
- Automatic fan cut-out when door is opened
- Automatic electric defrost with re-evaporation of defrost water
- Heavy duty cabinet
- Tested to Climate Class 5
- Exterior and interior of stainless steel AISI 304
- Anti-tilt shelf supports moulded into the inner lining
- LED lighting on the top panel
- Right hand hinged reversible door
- Automatic door closing
- Door lock
- Removable magnetic door gaskets
- Pedal door opener with overload protection (included as accessory)
- Pan-shaped inside base with rounded corners to catch fluids
- Low sound level
- IP21 water protection
- Matching design identity as the Premier counters

ENTHALTENES ZUBEHÖR

4 graue Roste (B650 x T530 mm), Pedal-Türöffner mit Überlastungsschutz

GARANTIEZEIT
6 Jahre Garantie auf Teile und Lohn

AUSSEN
Edelstahl AISI 304

INNENRAUM
Edelstahl AISI 304

Kältemittelkompatibilität: R448A, R449A, R452A

ZERTIFIZIERUNGEN

ISO HOSHIZAKI • ISO 9001
ISO HOSHIZAKI • ISO 14001
CE

Sonntag, 21 Dezember 2025, 13:52

Hoshizaki Europe B.V.
Burgemeester Stramanweg 101
1101 AA Amsterdam
The Netherlands

vertrieb@hoshizaki.de
www.hoshizaki-europe.com

Premier U 80 DR U Ru1

SPEZIFIKATIONEN

Rostmaß	Volumen, brutto	Elektrischer Anschluss	Min. cooling capacity K and M cabinets at -10°C	Temperature Range Span	Klimaklasse
2/1 GN Quer	700 L	230V, 50Hz	300 W	-25/+12°C	5

VERSANDANGABEN

Breite (verpackt)	Tiefe (verpackt)	Höhe (verpackt)	Volumen (verpackt)	Bruttogewicht	Breite	Tiefe	Höhe ein-schließlich Füße (mindestens)	Höhe ein-schließlich Füße (maximal)	Nettogewicht
870 mm	885 mm	2.250 mm	1,732 m3	115 kg	810 mm	728 mm	2.080 mm	2.130 mm	105 kg

Haftungsausschluss: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.



Hoshizaki Belgium info@hoshizaki.nl
Hoshizaki Danmark info@hoshizaki.dk
Hoshizaki Deutschland vertrieb@hoshizaki.de
Hoshizaki France info@hoshizaki.fr
Hoshizaki Iberia info@hoshizaki.es
Hoshizaki Italia commerciale@hoshizaki.it
Hoshizaki Middle East sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige orderSE@hoshizaki.dk
Hoshizaki UK uksales@hoshizaki.uk
Exportländer sales.ex@hoshizaki-europe.com
Andere Länder sales.ex@hoshizaki-europe.com

www.hoshizaki-europe.com