



HOSHIZAKI

Premier U 70 DR U Ru1 Refrigerator/Freezer 'U' type with RU1 valve for remote cooling system



2/1 GN

ACCESSORIES INCLUDED

3 grey shelves (530 x 650mm) + 1 bottom shelf, Pedal door opener with overload protection

OPTIONAL EXTRAS

Grey shelf with back guard

Grey bottom shelf with back guard

Stainless shelf with back guard

Stainless bottom shelf with back guard

Set of stainless shelves (3 top and 1 bottom) with back guard

Master key

PRODUCT SERIES: PREMIER 70

ITEM NUMBER: 188701031

COUNTRY OF ORIGIN: UK

Hoshizaki Premier U 70 DR U Ru1 is a 2/1 GN deep cabinet with RU1 valve for connection to a remote cooling system. It is ready to install and is compatible with multiple refrigerants. This heavy duty cabinet has a gross volume of 700 ltr. and the height of the cabinet with adjustable legs is 2080-2130mm. Adjustable legs are 130-180mm. The depth is 848 mm without pedal door opener (920 mm incl. pedal door opener).

Ultimate flexibility with 'U' type cabinet:

The cabinet can be set to run as a refrigerator or as a freezer. Set the controller to run as either K, M or F cabinet with the following temperature ranges:

K: +2/+12°C M: -5/+12°C F: -25/-5°C

- Ready-to-install cabinet with RU1 valve
- Air distribution system
- Automatic fan cut-out when door is opened
- Automatic electric defrost with re-evaporation of defrost water
- Heavy duty cabinet
- Tested to climate class 5
- Exterior and interior of stainless steel AISI 304
- Anti-tilt shelf supports moulded into the inner lining
- LED lighting on the top panel
- Right hand hinged reversible door
- Automatic door closing
- Door lock
- Removable magnetic door gaskets
- Pedal door opener with overload protection (included as accessory)
- Pan-shaped inside base with rounded corners to catch fluids
- Low sound level
- IP21 water protection
- Matching design identity as the Premier counters

WARRANTY PERIOD

1 Year on Parts

EXTERIOR

Stainless steel AISI 304

INTERIOR

Stainless steel AISI 304

Refrigerant compatibility: R448A, R449A, R455A

CERTIFICATIONS





HOSHIZAKI

Premier U 70 DR U Ru1

TECHNICAL SPECIFICATIONS


Shelf size	Volume, gross	Power supply	Min. cooling capacity K and M cabinets at -10°C	Temperature Range Span	Climate class
2/1 GN deep	700 l	230V, 50Hz	300 W	-25/+12°C	5 (max. ambient 40°C w/ 40% RH)

SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume (packed)	Gross weight	Width	Depth	Height	Height including legs (minimum)	Height including legs (maximum)	Net weight
750 mm	975 mm	2,150 mm	1.572 m3	115 kg	690 mm	848 mm	1,950 mm	2,080 mm	2,130 mm	105 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

Please observe: This cabinet for connection to remote cooling system is on special order only. Please take longer lead times into consideration



HOSHIZAKI

Hoshizaki Belgium
 Hoshizaki Danmark
 Hoshizaki Deutschland
 Hoshizaki France
 Hoshizaki Iberia
 Hoshizaki Italia
 Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com
soles.ex@hoshizaki-europe.com

Hoshizaki Netherlands
 Hoshizaki Norge
 Hoshizaki Sverige
 Hoshizaki UK
 Export countries
 Other countries

info@hoshizaki.nl
salg@hoshizaki.no
orderSE@hoshizaki.dk
uksales@hoshizaki.uk
sales.ex@hoshizaki-europe.com
sales.ex@hoshizaki-europe.com

www.hoshizaki-europe.com