



HOSHIZAKI

PREMIER TK600 CO2 1N BK NF

Technical kit module for blast chiller/freezer



PRODUCT SERIES: TECHNICAL KITS
ITEM NUMBER: 5LMA6GQRH-N4ALBC
COUNTRY OF ORIGIN: ITALY

PREMIER TK600 CO2 1N BK NF is a technical kit for roll-in blast chiller/freezer system.

Chilling/freezing capacity of 600/400 kg. It features a user friendly 7" touch controller display.

The module is equipped with controller, heated core probe, Wi-Fi connection, Ethernet-port, USB-port, drip collection tray and feet.

- For connection to external cooling system and compatible with CO2 refrigerant.
- Cooling functions: Chilling, freezing, preservation, precooling, ice cream hardening, fish sanitation, bottle cooling, pastry, cell sanitation
- 'Hot' functions: Thawing, cell drying
- 7" touch screen controller with coloured icons
- Choice of time- or temperature-controlled (probe) chill/freeze cycles
- Single probe cascade cycles, Timer cycles, Quick start
- Heated core probe
- Can be connected to Wi-fi
- Ethernet port
- USB-port for HACCP data collection
- Customisable parameters
- Multiple and customisable cycle stages
- Adjustable fan speed
- Heater defrosting
- Electric expansion valve w/driver
- Built for climate class 5 cooling system operating in ambient temperatures up to +40°C
- Internal fan section can be opened for easy cleaning around and behind
- Evaporator with cataphoresis coating for rust protection
- Main power switch
- Front access to electrical box
- Smart connectors for seamless installation and interconnection with other products in the range

OPTIONAL EXTRAS

- Evaporator bumper *
- Remote controller *
- Ozone generator *
- Wooden crate packaging *
- Wooden cage packaging *

* Add-on = Must be specified when placing the order

WARRANTY PERIOD

**1 Year on Parts & Labour -
based on country agreement**

EXTERIOR

Stainless steel AISI 304

Refrigerant compatibility: R744



HOSHIZAKI

PREMIER TK600 CO2 1N BK NF

TECHNICAL SPECIFICATIONS

Cooling system	Temperature range	Climate class	Power supply	Required cooling capacity	Maximum system pressure	Connection load	Fuse Rating	Chilling capacity (from +70°C to +3°C in 90 minutes)	Freezing capacity (from +70°C to -18°C in 4 hours)
For remote cooling system	-40/+40°C	5 (max. ambient 40°C w/ 40% RH)	1/220 - 240V/50Hz	74,000 W	60 Bar	2,040 W	40 A	600 kg	400 kg

Net weight	Height including legs (minimum)	Height including legs (maximum)	Dimensions external (W x D x H)
364 kg	2,094 mm	2,139 mm	4,060 mm x 410 mm x 2,094 mm

SHIPPING SPECIFICATIONS

Dimensions packed (W x D x H)	Volume (packed)	Gross weight
1,050 mm x 2,270 mm x 2,240 mm	5.3 m ³	516 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.



HOSHIZAKI

Hoshizaki Belgium info@hoshizaki.nl
Hoshizaki Danmark info@hoshizaki.dk
Hoshizaki Deutschland vertrieb@hoshizaki.de
Hoshizaki France info@hoshizaki.fr
Hoshizaki Iberia info@hoshizaki.es
Hoshizaki Italia commerciale@hoshizaki.it
Hoshizaki Middle East sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige orderSE@hoshizaki.dk
Hoshizaki UK uksales@hoshizaki.uk
Export countries sales.ex@hoshizaki-europe.com
Other countries sales.ex@hoshizaki-europe.com

www.hoshizaki-europe.com

