



HOSHIZAKI

ECO TWIN KG 82 CCF CO2 L2 4S A (Carel)



PRODUCT SERIES: SUPERIOR - ECO
ITEM NUMBER: 960819001

FOR REMOTE CO2 COOLING SYSTEMS.

Ready-to-install cabinet with factory fitted CAREL controller.


Solution includes:

Controller Carel MPXpro and user terminal display. Pressure tested evaporator PS 60 bar. Pressure test documentation supplied.
Sensors, 3 pcs PT 1000 for: Room, Evaporator and Superheat temperature. Electrical box mounted with DIN controller. Electrical components are all connected inside the controller box (EMC & LVD tested). Injection valve (AKVP with EEV coil) for maximum opening torque. Pressure transmitter (0-45 bar gauge). Standard is factory fitted re-evaporation tray underneath the cabinet including heater for re-evaporation of defrost water. If external drain is available it is recommended to connect to it.

Extended option: The controller is prepared for external monitoring by RS 485.

Key features:

- The controller is concealed behind the top panel, protected against splashing water.
- Design principle of "no broken surfaces" makes the cabinets easy to clean.
- The distinctive aluminium profiles stretching from top to bottom on both sides of the cabinet impart strength and enhance appearance.
- The modular rails can go directly in the dishwasher.
- Pedal door opener for hands-free operation.
- Suitable for the wide 2/1 GN system



EXTERIOR
Stainless Steel

INTERIOR
Stainless

Refrigerant type: R744

| Energy efficiency class |
|----------------------------|
| Category not yet regulated |



HOSHIZAKI

ECO TWIN KG 82 CCF CO2 L2 4S A (Carel)

TECHNICAL SPECIFICATIONS

| Temperature range | Shelf size | Volume, gross | Net usable volume | Power supply |
|-------------------|-------------|---------------|-------------------|--------------|
| +2/+12°C | 2/1 GN wide | 614 l | 462 l | 230V, 50Hz |

SHIPPING SPECIFICATIONS

| Gross weight | Width | Depth | Height | Net weight |
|--------------|--------|--------|----------|------------|
| 157 kg | 820 mm | 785 mm | 2.125 mm | 157 kg |



Dimensional drawing coming soon



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige order@hoshizaki.se
Hoshizaki UK uksales@hoshizaki.uk
Export countries sales.ex@hoshizaki-europe.com
Other countries sales.ex@hoshizaki-europe.com

www.hoshizaki-europe.com