



# HOSHIZAKI

## ECO TWIN U 82 CCF CO2 L2 4S A (29X71)



PRODUCT SERIES: SUPERIOR - ECO  
ITEM NUMBER: 960829000

FOR REMOTE CO2 COOLING SYSTEMS.

Cabinet without factory fitted controller. Allows for easy integration of your own preferred controller.

Solution includes:

Pressure tested evaporator PS 60 bar. Pressure test documentation supplied.  
Sensors, 3 pcs PT 1000 for: Room, Evaporator and Superheat temperature. Electrical Box prepared for mounting of DIN controller. Standard electrical components are connected to a plinth inside the controller box for easy fitting of an alternative controller. Injection valve (AKVP with EEV coil) for maximum opening torque. Standard controller display cut-out, size H29 x W71 mm. Standard is factory fitted re-evaporation tray underneath the cabinet including heater for re-evaporation of defrost water. If external drain is available it is recommended to connect to it.

Optional on request: Customized controller display cut-out in the control box.

Provided and installed by cooling contractor:

Controller: Not factory fitted - Installer's choice  
Pressure transmitter

Ultimate flexibility with 'U' type cabinet:

This cabinet can be used for building a refrigerator or a freezer. It comes equipped with all needed components ( heaters, fan etc.). The installer just has to add the controller of his choice.

**EXTERIOR  
Stainless Steel**

**INTERIOR  
Stainless**

- against splashing water.
- Design principle of "no broken surface"
- The distinctive aluminium profiles stretch the cabinet impart strength and enhance
- The modular rails can go directly in the
- Pedal door opener for hands-free operation.
- Suitable for the wide 2/1 GN system

Refrigerant type: R744

**Energy efficiency class**

Category not yet regulated



# HOSHIZAKI

## ECO TWIN U 82 CCF CO2 L2 4S A (29X71)

### TECHNICAL SPECIFICATIONS

Temperature range	Shelf size	Volume, gross	Net usable volume	Volume, net	Power supply
-5/+12°C	2/1 GN wide	614 l	451 l	451 l	230V, 50Hz

### SHIPPING SPECIFICATIONS

Gross weight	Width	Depth	Height	Net weight
136 kg	820 mm	785 mm	2,125 mm	136 kg



Dimensional drawing coming soon



## HOSHIZAKI

Hoshizaki Belgium  
Hoshizaki Danmark  
Hoshizaki Deutschland  
Hoshizaki France  
Hoshizaki Iberia  
Hoshizaki Italia  
Hoshizaki Middle East

[info@hoshizaki.nl](mailto:info@hoshizaki.nl)  
[info@hoshizaki.dk](mailto:info@hoshizaki.dk)  
[vertrieb@hoshizaki.de](mailto:vertrieb@hoshizaki.de)  
[info@hoshizaki.fr](mailto:info@hoshizaki.fr)  
[info@hoshizaki.es](mailto:info@hoshizaki.es)  
[commerciale@hoshizaki.it](mailto:commerciale@hoshizaki.it)  
[sales.ex@hoshizaki-europe.com](mailto:sales.ex@hoshizaki-europe.com)

Hoshizaki Netherlands [info@hoshizaki.nl](mailto:info@hoshizaki.nl)  
Hoshizaki Norge [salg@hoshizaki.no](mailto:salg@hoshizaki.no)  
Hoshizaki Sverige [orderSE@hoshizaki.dk](mailto:orderSE@hoshizaki.dk)  
Hoshizaki UK [uksales@hoshizaki.uk](mailto:uksales@hoshizaki.uk)  
Export countries [sales.ex@hoshizaki-europe.com](mailto:sales.ex@hoshizaki-europe.com)  
Other countries [sales.ex@hoshizaki-europe.com](mailto:sales.ex@hoshizaki-europe.com)

[www.hoshizaki-europe.com](http://www.hoshizaki-europe.com)