

# **IM-130CPE**

# **Cuber, Self Contained**

Production Capacity (kg/24h) - AT 10°C, WT 10°C: 108 Storage bin capacity: 38 kg



ICE TYPE: Large cubes, Standard



#### **ACCESSORIES INCLUDED**

Installation kit, Scoop

## **OPTIONAL EXTRAS**

4HC-H water filtration, scoop holder kit, UV-C sanitization kit

## **CORRESPONDING WATER FILTERS**

4HC-H Twin Water Filter, 4HC Replacement Cartridge

PRODUCT SERIES: IM 130 ITEM NUMBER: M116 COUNTRY OF ORIGIN: UK

Hoshizaki IM-130CPE Cube model is a self-contained ice maker producing up to 108 kg of cube ice per 24 hours.

Ice cube dimensions and weight - disclaimer: The drawing is for illustration purposes only. Cube size and weight may be differ due to local installation conditions

- Ice making system with an automatic rinse cycle
- Each ice cycle is made with fresh water
- Closed Cell System helps produce compact, hard and geometrically perfect
- Closed water circuit for contamination protection
- Easy external access to control panel
- UV-C sanitization function is retrofittable
- System comes with a magnetic DC water pump with variable speed that has no direct coupling, which prevents any leakage
- · Cleanable air filter
- Removable door gasket
- Easily removable water pan assembly

WARRANTY PERIOD 3 Years on Parts & Labour based on country agreement **EXTERIOR** 

Stainless steel AISI 441, Galvanized steel (Rear)

Refrigerant type: R290 / Refrigerant: 0.125 kg / CO2 equivalent: 0.375

#### **OPERATING CONDITIONS**

Ambient temperature (minimum): 1 °C, Ambient temperature (maximum): 40 °C, Water supply pressure (minimum): 0.07MPa (0.7bar), Water supply pressure (maximum): 0.8MPa (8bar), Water supply temperature (minimum): 5 °C, Water supply temperature (maximum): 35 °C, Voltage range: Rated Voltage ±6%

**CERTIFICATIONS** 


















# **IM-130CPE**







#### **TECHNICAL SPECIFICATIONS**

Cooling system	Power supply	Electrical circuit breaker protection	Heat Rejection (AT 32°C, WT 21°C)	Production Capacity (kg/24h) - AT 10°C, WT 10°C	Production Capacity (kg/24h) - AT 21°C, WT 15°C	Production Capacity (kg/24h) - AT 32°C, WT 21°C	Water consumption (m3/24h) - AT 10°C, WT 10°C
Air Cooled	1/220 - 240V/50Hz	5 A	1.45 kW	108	99	89	0.43

#### SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume (packed)	Gross weight	Width (legs excluded)	Depth (legs excluded)	Height (legs excluded)	Dimensions legs	Net weight
1,110 mm	700 mm	875 mm	0.68 m3	91 kg	1,004 mm	600 mm	700 mm	for legs add 100mm	80 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.



Hoshizaki Belgium Hoshizaki Danmark Hoshizaki Deutschland Hoshizaki France Hoshizaki Iberia Hoshizaki Italia Hoshizaki Middle East info@hoshizaki.nl info@hoshizaki.dk vertrieb@hoshizaki.de info@hoshizaki.fr info@hoshizaki.es commerciale@hoshizaki.it sales.ex@hoshizaki-europe.com Hoshizaki Netherlands Hoshizaki Norge Hoshizaki Sverige Hoshizaki UK Export countries Other countries info@hoshizaki.nl salg@hoshizaki.no orderSE@hoshizaki.dk uksales@hoshizaki.uk sales.ex@hoshizaki-europe.com sales.ex@hoshizaki-europe.com

www.hoshizaki-europe.com