

## IM-240PE-F


### Cuber, Self Contained

**Production Capacity (kg/24h) - AT 10°C, WT 10°C: 210**

**Storage bin capacity: 110 kg**



**ICE TYPE: Large cubes, Standard**



#### ACCESSORIES INCLUDED

Installation kit, Legs, Scoop

#### OPTIONAL EXTRAS

4HC-H water filtration, UV-C sanitization kit

#### CORRESPONDING WATER FILTERS

4HC-H Twin Water Filter, 4HC Replacement Cartridge

PRODUCT SERIES: CUBE ICEMAKERS

ITEM NUMBER: M118-D100

COUNTRY OF ORIGIN: UK

Hoshizaki IM-240PE-F FlexiCube model is a self-contained ice maker with internal drain pump producing up to 210 kg of cube ice per 24 hours.

Ice cube dimensions and weight - disclaimer: The drawing is for illustration purposes only. Cube size and weight may be differ due to local installation conditions.

- Ice making system with an automatic rinse cycle
- Each ice cycle is made with fresh water
- Closed Cell System helps produce compact, hard and geometrically perfect ice
- Closed water circuit for contamination protection
- Easy external access to control panel
- Internal drain pump
- UV-C sanitization function is retrofittable
- System comes with a magnetic DC water pump with variable speed that has no direct coupling, which prevents any leakage
- Cleanable air filter
- Removable door gasket
- Easily removable water pan assembly

#### WARRANTY PERIOD

**3 Years on Parts & Labour -  
based on country agreement**

#### EXTERIOR

**Stainless steel AISI 441, Galvanized steel  
(Rear)**

Refrigerant type: R290 / Refrigerant: 0,147 kg / CO2 equivalent: 0,441 kg


#### OPERATING CONDITIONS

Ambient temperature (minimum): 1 °C, Ambient temperature (maximum): 40 °C, Water supply pressure (minimum): 0.07MPa (0.7bar), Water supply pressure (maximum): 0.8MPa (8bar), Water supply temperature (minimum): 5 °C, Water supply temperature (maximum): 35 °C, Voltage range (Rated Voltage): ±6%

#### CERTIFICATIONS



## IM-240PE-F



### TECHNICAL SPECIFICATIONS

| Cooling system | Power supply      | Electric Consumption | Electrical circuit breaker protection | Heat Rejection (AT 32°C, WT 21°C) | Production Capacity (kg/24h) - AT 10°C, WT 10°C | Production Capacity (kg/24h) - AT 21°C, WT 15°C | Production Capacity (kg/24h) - AT 32°C, WT 21°C | Water consumption (m3/24h) - AT 10°C, WT 10°C |
|----------------|-------------------|----------------------|---------------------------------------|-----------------------------------|-------------------------------------------------|-------------------------------------------------|-------------------------------------------------|-----------------------------------------------|
| Air Cooled     | 1/220 - 240V/50Hz | 0,87 kW              | 5 A                                   | 2,58 kW                           | 210                                             | 195                                             | 175                                             | 0,67                                          |

### SHIPPING SPECIFICATIONS

| Width (packed) | Depth (packed) | Height (packed) | Volume (packed) | Gross weight | Width  | Depth  | Height   | Dimensions legs       | Net weight |
|----------------|----------------|-----------------|-----------------|--------------|--------|--------|----------|-----------------------|------------|
| 805 mm         | 760 mm         | 1.684 mm        | 1,03 m3         | 122 kg       | 704 mm | 665 mm | 1.510 mm | for legs add 70-110mm | 109 kg     |

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.