


HNC-210BE-R-BLH

**Sushi display case with LED lighting,
right-sided**



ACCESSORIES INCLUDED

ABS tray (large) x 5, ABS tray (small) x 1

OPTIONAL EXTRAS

N/A

PRODUCT SERIES: HNC 210
ITEM NUMBER: S058-C174
COUNTRY OF ORIGIN: JAPAN

This Hoshizaki HNC-210BE-R-BLH is a Sushi Case with condenser unit on the right (right-sided). It has a net volume of 87 litr. and a cabinet width of 2100 mm. Equipped with a sliding door with 150 mm height towards the operator, LED lighting, thermometer and lightweight ABS trays.

- Self-contained unit
- Refrigerated glass display
- Top glass angles down, allowing for plate space on top of units
- Antiscattering film on glass
- Smooth airflow, without forced air-circulation
- Condenser airflow is in the back and out the side
- Large condenser face improves cooling performance
- The tubular-shaped evaporator absorbs the heat continuously (no dripping)
- Solid food trays with radius groove to fit sushi foods
- The elevated side wings of the trays allow more air circulation
- LED lighting
- Thermometer inside the cabinet
- The sliding door and the ABS trays are easily disassembled and removed for daily cleaning.
- Not intended to be used as a cooling storage cabinet.

WARRANTY PERIOD

**2 Years on Parts & Labour -
based on country agreement**

EXTERIOR

**Clear Glass, ABS Plastic,
PVC Plastic**

INTERIOR

**Clear Glass, ABS Plastic,
Stainless Steel**

Refrigerant type: R600a / Refrigerant: 0,048 kg / CO2 equivalent:
0,144 kg / GWP: 3 GWP

OPERATING CONDITIONS

Ambient temperature (minimum): 10 °C, Ambient temperature (maximum):
30 °C


CERTIFICATIONS





HOSHIZAKI

HNC-210BE-R-BLH



TECHNICAL SPECIFICATIONS

Cooling system	Temperature retention (6h)	Power supply	Connection load	Electric Consumption	Heat Rejection (AT 32 °C, WT 21 °C)
Built-in cooling system	5 °C	1/220 - 240V/50Hz	155 W	0,155 kW	0,43 kW

Volume, net	Dimensions internal (W x D x H)	Compressor	LED
87 l	845 mm x 288 mm x 157 mm	Right side	Including LED

SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume (packed)	Gross weight	Width	Depth	Height	Net weight
2.180 mm	415 mm	517 mm	0,468 m3	68 kg	2.100 mm	345 mm	270 mm	47 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

Please observe: Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper airflow and pipe connections).



Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands
Hoshizaki Norge
Hoshizaki Sverige
Hoshizaki UK
Export countries
Other countries
info@hoshizaki.nl
salg@hoshizaki.no
order@hoshizaki.se
uksales@hoshizaki.uk
sales.ex@hoshizaki-europe.com
sales.ex@hoshizaki-europe.com
www.hoshizaki-europe.com