

KPS 60 CF CO2

ROLL-IN BLAST CHILLER (CF) FOR REMOTE CO2 COOLING SYSTEMS.



PRODUCT SERIES: KPS
ITEM NUMBER: 860600505

ROLL-IN BLAST CHILLER (CF) FOR REMOTE CO2 COOLING SYSTEMS.

Ready-to-install blast chiller with factory fitted master and slave controller.

Solution includes:

Master controller and superheat controller (slave).Expansion valvePressure transmitter

External drain: It is necessary to connect this unit to an external drain.

General description: • Multipoint probe with 3 measuring points • Choose either the IFR operation, time or temperature controlled chill cycle. • Prevent surface freezing damage with the IFR blast chilling function. • Up to 20 customized cycles can be stored. • HACCP alarms • Operates as a storage cabinet after the chilling process has finished.

EXTERIOR
Stainless Steel

INTERIOR
Stainless

Refrigerant type: R744



HOSHIZAKI

KPS 60 CF CO2

TECHNICAL SPECIFICATIONS

Temperature range	Power supply	Chilling capacity (from +70°C to +3°C in 90 minutes)
-25/+10°C	230V, 50Hz	60 kg

Dimensions internal (W x D x H)
455 mm x 850 mm x 1,545 mm

SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume (packed)	Gross weight
780 mm	995 mm	2,025 mm	1.572 m3	205 kg



Dimensional drawing coming soon



HOSHIZAKI

Hoshizaki Middle East

sales.ex@hoshizaki-europe.com

www.hoshizaki-europe.com