

SUR-65DG-C-C

1-Door Refrigerated Cabinet, HC



PRODUCT SERIES: SNOWFLAKE GII
ITEM NUMBER: 877000825

The Snowflake GII series is brought to you by Japanese and Danish engineering excellence, dedicated to simplifying the day-to-day work routines of kitchen staffs all around the world.

The technology behind the performance boost of Snowflake GII is the tropicalised cooling system enduring up to +40°C. Additionally, the cooling agent of the new generation of Snowflake is the eco-friendly refrigerant R290, a natural gas (HC) that enhances the performance and cuts down energy consumption significantly.

Both interior and exterior are built of anti-corrosion stainless steel AISI 304, which is among the best choices for hygienic and food safe cooking environments.

The Snowflake GII SUR-65BG is a 1-door refrigerated cabinet with a net internal volume of 403 Ltr.

As a product that is designed and built to last, this refrigerated cabinet combines an innovative design concept, premium materials and clever extras:

- Minimum cool air lost: double insulated and extra wide door gaskets help to keep the cold air into the cabinet
- Both interior and exterior are built of stainless steel AISI 304, which is among the best choices for hygienic and food safe cooking environments
- Anti-tilt mechanism: moulded liners for saver container and rooster handling
- Reversible doors for maximum flexibility
- Removable gaskets make sure you can clean the device thoroughly
- This and other thoughtful extras, such as the cleaning-free condenser, are designed to reduce kitchen cleaning times whilst storing foods protectively in the best possible way

The refrigerant used in all Snowflake GII HC models is R290. This agent is a natural gas which enhances the performance of the refrigerated counter and has, compared to other refrigerants, a minimal ozone depletion potential. R290 is one of the view refrigerants compliant with the called F-Gas Regulation, issued by the European Commission. This regulation aims to phase out HFCs

EXTERIOR

Stainless steel AISI 304

INTERIOR

Stainless steel AISI 304

Refrigerant type: R290

Energy consumption	Energy efficiency class
2 kWh	D



HOSHIZAKI

SUR-65DG-C-C

TECHNICAL SPECIFICATIONS

Temperature range	Shelf size	Volume, gross	Power supply	Connection load	Climate class
-2/+8°C	2/1 GN deep	560 l	230V, 50Hz	0.17 kW	5 (max. ambient 40°C w/ 40% RH)

SHIPPING SPECIFICATIONS

Gross weight	Width	Depth	Height	Net weight
131 kg	654 mm	840 mm	1,996 mm	131 kg



Dimensional drawing coming soon



HOSHIZAKI

Hoshizaki Middle East

sales.ex@hoshizaki-europe.com

www.hoshizaki-europe.com