



# BEERMATIC DualTap DBF-AS65WE-EU

## Beer Dispenser



## ACCESSORIES INCLUDED

Drain pan x 2, Grille x 2, Platform x 2

ITEM NUMBER: B078-D011

The HOSHIZAKI BEERMATIC DUAL TAP is a fully automatic Draft Beer Dispenser with foaming mechanism. This counter top model has two separate circuits. This means two different types of beer can be served at the same time. The hands-free portion control allows a pre-set quantity of chilled draft beer and foam to be served at the push of a button. This dispenser is great for cafes, restaurants, pubs, temporary bars, outdoor beer gardens, event venues, event catering, vending opportunities.


Perfect portioning: The beer -to-foam ratio can be adjusted for different types of beer or to meet local preferences and requirements. The automatic tilting unit is compatible with all common jug or glass sizes (50 mm or more in inside diameter and 105 mm or less in outside diameter).

Perfect taste and temperature: An internal cooling system chills down the beer on its way from the keg through the machine. That means the draft beer can be served directly from ambient temperature kegs.

**Cost and waste control:** The beer is dispensed first, followed by foam which is poured from a separate spout. Thus, portion control can be very accurate, without spillage of beer and/or froth. Saving you up to 8 half-liter beers per 30 liter keg, the BeerMatic is a great tool for cost and waste control. Additionally, portion counter monitors the number of portions served.

**Hygiene & Food Safety:** As spillage is avoided entirely, the work space remains clean at all times. The dispenser's compartmentalized design is engineered to avoid contamination. The cleaning of the beer dispenser is a quick and easy process.

Perfect fit: With its compact design and small foot print this countertop dispenser fits into multiple environments. It can also be easily transported and installed for non-



- Two different types of beer can be served at one time
- Hand-free operation and CO<sub>2</sub> equivalent: 250 kg
- Manual pouring can be quickly implemented
- Dispensing rate 4 jugs per minute. A portion counter monitors the number of portions served
- Designed for high-volume outlets. After initial freeze down 65 lt of beer can be served consecutively in 4 hours
- Recovery time: 45 minutes. Quantity available after recovery time: 10.2 lt

- Manually raising or lowering the glass support base to the desired distance

from each output  
fold  
to the  
with

**ISO** **CE** **EAC** **ISO**

HOSHIZAKA ISO 9001 HOSHIZAKA ISO 14001

in outside diameter.

located base, be the same from each  
or more in inside diameter 100 mm or less



# HOSHIZAKI

## BEERMATIC DualTap DBF-AS65WE-EU



Dimensional drawing coming soon

### TECHNICAL SPECIFICATIONS

Cooling system	Power supply	Energy consumption	Flow Rate (2.0 - 3.5 bar)	Instant Output after 45 minutes recovery time	Instant output in 4 hours after initial freeze down period of 10 hours	Recovery time
Air Cooled	1/220 - 240V/50Hz	0.345 kWh	0.034-0.049 ml/s	10.2 l	65 l	45 m

### SHIPPING SPECIFICATIONS

Gross weight	Width	Depth	Height	Net weight
56 kg	367 mm	674 mm	764 mm	50 kg



# HOSHIZAKI

Hoshizaki Middle East

[sales.ex@hoshizaki-europe.com](mailto:sales.ex@hoshizaki-europe.com)

[www.hoshizaki-europe.com](http://www.hoshizaki-europe.com)