

DIM-30DE-2(SA)

Dispenser, Ice Only

Production Capacity (kg/24h) - AT 10°C, WT 10°C: 42

Storage bin capacity: 15 kg



ICE TYPE: Large cubes, Standard

ACCESSORIES INCLUDED

Installation kit, Mounting Brace (Wall Mounting)

OPTIONAL EXTRAS

4HC-H water filtration, Mounting Brace (Floor mounting)

CORRESPONDING WATER FILTERS

4HC-H Single Water Filter, 4HC Replacement Cartridge

PRODUCT SERIES: DIM 40
ITEM NUMBER: E2HA-D810

The DIM-30DE-2 produces cubed ice and has a new exterior design. The freshly produced ice does not come in contact with light or air when stored and therefore maintains the highest quality. Its ice is very well suited for multiple environments including food and beverage, catering, leisure and healthcare. The portion control can be easily set, making it easy to regulate the consumption of ice among end-users, therefore ideal for a self-serving environment.

- Hoshizaki ice dispensers are more compact with reduced space requirements and in line with modern interiors.
- Ice dispensing system includes lever and LED operation buttons, easy and simple to use, therefore ideal for self-serving environment.
- New lever design prevents touching the lip of a glass, minimising risk of bacterial transfer.

WARRANTY PERIOD

2 Years on Parts & Labour

EXTERIOR

Acrylic Baked Steel (Cabinet), ABS Molding (Front and Back Panel)

Refrigerant type: R134a / Refrigerant: 0.2 kg / CO2 equivalent: 286 kg

OPERATING CONDITIONS

Ambient temperature (minimum): 1 °C, Ambient temperature (maximum): 40 °C, Water supply pressure (minimum): 0.07MPa (0.7bar), Water supply pressure (maximum): 0.78MPa (7.8bar), Water supply temperature (minimum): 5 °C, Water supply temperature (maximum): 35 °C, Voltage range: Rated Voltage $\pm 6/10\%$

CERTIFICATIONS



DIM-30DE-2(SA)



Dimensional drawing coming soon

TECHNICAL SPECIFICATIONS

Cooling system	Power supply	Electric Consumption	Electrical circuit breaker protection	Heat Rejection (AT 32°C, WT 21°C)	Production Capacity (kg/24h) - AT 10°C, WT 10°C	Production Capacity (kg/24h) - AT 21°C, WT 15°C	Production Capacity (kg/24h) - AT 32°C, WT 21°C	Water consumption (m3/24h) - AT 10°C, WT 10°C
Air Cooled	1/220-240V, 50/60Hz	0.32 kW	5 A	0.6 kW	42	36	30	0.15

SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume (packed)	Volume, gross	Gross weight	Width	Depth	Height including legs (minimum)	Height including legs (maximum)	Net weight
450 mm	730 mm	1,666 mm	0.547 m3	0.55 l	80 kg	350 mm	526 mm	1,590 mm	1,635 mm	65 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.