

# IM-21CNE-HC

# Cuber, Self Contained

Production Capacity (kg/24h) - AT 10°C, WT 10°C: 25 Storage bin capacity: 11.5 kg



ICE TYPE: Large cubes, Standard



## ACCESSORIES INCLUDED

Installation kit, Scoop

#### OPTIONAL EXTRAS

4HC-H water filtration, external drain pump, legs

## **CORRESPONDING WATER FILTERS**

4HC-H Single Water Filter, 4HC Replacement Cartridge

PRODUCT SERIES: IM, IM 21 ITEM NUMBER: M061 COUNTRY OF ORIGIN: UK

Hoshizaki IM-21CNE-HC is a self-contained ice maker producing up to 25 kg of cube ice per 24 hours.

Ice cube dimensions and weight - disclaimer: The drawing is for illustration purposes only. Cube size and weight may be differ due to local installation conditions.

- Ice making system with an automatic rinse cycle
- Each ice cycle is made with fresh water
- Closed Cell System helps produce compact, hard and geometrically perfect ice
- Closed water circuit for contamination protection
- Electronic controller
- System comes with a magnetic water pump that has no direct coupling, which prevents any leakage
- Cleanable air filter
- Removable door gasket

WARRANTY PERIOD
2 Years on Parts & Labour

EXTERIOR Stainless steel AISI 441, Galvanized steel (Rear)

Refrigerant type: R290 / Refrigerant: 0.055 kg / CO2 equivalent: 0.165 kg

#### **OPERATING CONDITIONS**

Ambient temperature (minimum): 1 °C, Ambient temperature (maximum): 40 °C, Water supply pressure (minimum): 0.07MPa (0.7bar), Water supply pressure (maximum): 0.8MPa (8bar), Water supply temperature (minimum): 5 °C, Water supply temperature (maximum): 35 °C, Voltage range: Rated Voltage ±6%

#### CERTIFICATIONS



Thursday, 17 July 2025, 20:13

Hoshizaki Europe B.V. Burgemeester Stramanweg 101 1101 AA Amsterdam The Netherlands T. +31 (0)20 691 8499 sales.ex@hoshizaki-europe.com www.hoshizaki-europe.com



# IM-21CNE-HC





# TECHNICAL SPECIFICATIONS

Cooling system	Sound level	Power supply	Energy consumption	Electrical circuit breaker protection	Heat Rejection (AT 32°C, WT 21°C)	Production Capacity (kg/24h) - AT 10°C, WT 10°C	Production Capacity (kg/24h) - AT 21°C, WT 15°C	Production Capacity (kg/24h) - AT 32°C, WT 21°C	Water consumption (m3/24h) - AT 10°C, WT 10°C
Air Cooled	51.1 dB	1/220 - 240V/50Hz	0.225 kWh	5 A	0.51 kW	25	24	22	0.1

## SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume, gross	Gross weight	Width	Depth	Height	Dimensions legs	Net weight
505 mm	575 mm	862 mm	0.25	39 kg	398 mm	451 mm	695 mm	Optional: 90-135 mm extra	34 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice. Please observe: Legs sold separately - contact our sales office for pricing

HOSHIZAKI

Hoshizaki Middle East sales

st <u>sales.ex@hoshizaki-europe.com</u>