



# HOSHIZAKI

## IM-240DPE-U

### Cuber, Modular & Stackable

Production Capacity (kg/24h) - AT 10°C, WT 10°C: 210

PRODUCT SERIES: CUBE ICEMAKERS

ITEM NUMBER: M120-D200

COUNTRY OF ORIGIN: UK


Hoshizaki IM-240DPE-U UltraCube model is a modular and stackable ice maker with UVC sanitization function producing up to 210 kg of cube ice per 24 hours. This model is compatible with Hoshizaki storage bins.

Ice cube dimensions and weight - disclaimer: The drawing is for illustration purposes only. Cube size and weight may differ due to local installation conditions.

- Ice making system with an automatic rinse cycle.
- Each ice cycle is made with fresh water.
- Closed water circuit for contamination protection.
- Closed Cell System helps produce compact, hard and geometrically perfect ice.
- Easy external access to control panel.
- System comes with a magnetic DC water pump with variable speed and that has no direct coupling, which prevents any leakage.
- UV sanitization function sanitizing air and water (UV-C irradiation).
- Cleanable air filter.
- Stainless steel frame inside.
- Easily removable water pan assembly.
- A maximum of 3 units are stackable: 1 x DPE + 2 x XPE



ICE TYPE: Large cubes, Standard



Cube Size: **STANDARD**  
Weight: 23 g

**WARRANTY PERIOD**  
**3 Years on Parts & Labour**

**EXTERIOR**  
Stainless steel AISI 441, Galvanized steel (Rear)

Refrigerant type: R290 / Refrigerant: 0.147 kg / CO2 equivalent: 0.441 kg

**OPERATING CONDITIONS**  
Ambient temperature (minimum): 1 °C, Ambient temperature (maximum): 40 °C, Water supply pressure (minimum): 0.07MPa (0.7bar), Water supply pressure (maximum): 0.8MPa (8bar), Water supply temperature (minimum): 5 °C, Water supply temperature (maximum): 35 °C, Voltage range (Rated Voltage): ±6%

**ACCESSORIES INCLUDED**  
brace, Installation kit, Scoop

**OPTIONAL EXTRAS**  
4HC-H water filtration, compatibility kit for stacking combinations including new and previous N series ice makers.

**CORRESPONDING WATER FILTERS**  
4HC-H Twin Water Filter, 4HC Replacement Cartridge

**CORRESPONDING BIN(S)**  
B-340SB

**CORRESPONDING TOP KITS**  
TK-48 for B-340SB (optional, not required), TK-IMD2 for B-340SB

#### CERTIFICATIONS





# HOSHIZAKI

## IM-240DPE-U



### TECHNICAL SPECIFICATIONS

| Cooling system | Power supply      | Electrical circuit breaker protection | Heat Rejection (AT 32°C, WT 21°C) | Production Capacity (kg/24h) - AT 10°C, WT 10°C | Production Capacity (kg/24h) - AT 21°C, WT 15°C | Production Capacity (kg/24h) - AT 32°C, WT 21°C | Water consumption (m <sup>3</sup> /24h) - AT 10°C, WT 10°C |
|----------------|-------------------|---------------------------------------|-----------------------------------|---|---|---|--|
| Air Cooled     | 1/220 - 240V/50Hz | 5 A                                   | 2.25 kW                           | 210   | 195   | 175   | 0.67   |

### SHIPPING SPECIFICATIONS

| Width (packed) | Depth (packed) | Height (packed) | Volume (packed)      | Gross weight | Width    | Depth  | Height | Net weight |
|----------------|----------------|-----------------|----------------------|--------------|----------|--------|--------|------------|
| 1,196 mm       | 825 mm         | 640 mm          | 0.632 m <sup>3</sup> | 96 kg        | 1,084 mm | 700 mm | 500 mm | 82 kg      |

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

Hoshizaki Middle East

[sales.ex@hoshizaki-europe.com](mailto:sales.ex@hoshizaki-europe.com)



# HOSHIZAKI

[www.hoshizaki-europe.com](http://www.hoshizaki-europe.com)