



HOSHIZAKI

B-140SB

Ice storage Bin

Storage bin capacity: 140 kg



ACCESSORIES INCLUDED

Legs, Scoop, Scoop holder

OPTIONAL EXTRAS

Topkit TK-30 (insulation strip for extra insulation)

PRODUCT SERIES: STORAGE BINS

ITEM NUMBER: M190

COUNTRY OF ORIGIN: UK

The B-140SB storage bin with a max. storage capacity of 140 kg configures with below mentioned modular cube and flake Ice makers. The door is fitted with gasket for high thermal efficiency.

The bin configures with icemakers W56cm:

IM-130A, IM-240A

FM-150/300/480/600

KMD-210, KMD-270

Top kits required: No

- Slim-line width 56 cm, fits nicely even in tight spaces
- Sturdy construction
- Upward opening door fitted with an insulating gasket
- Easy removable gasket for cleaning or replacement
- ABS plastic, light-weight, insulated door
- Door opening angle allows for stable rest position during ice scooping
- Stainless steel front and sides
- Non-corrosive innerlining of polyethylene
- Innerlining with rounded corners allows for faster collection of ice
- Rounded and smooth surfaces
- Adjustable legs 90-135 mm
- Back-panel drain connection
- FCM compliant (Food Contact Material)

WARRANTY PERIOD

2 Years on Parts & Labour

EXTERIOR

Stainless steel, galvanized steel (rear), plastic door

INTERIOR

Polyethylene


CERTIFICATIONS





HOSHIZAKI

B-140SB



TECHNICAL SPECIFICATIONS

| Width | Depth | Height | Dimensions legs | Net weight | Storage bin capacity |
|--------|--------|----------|------------------------|------------|----------------------|
| 559 mm | 820 mm | 1,016 mm | For legs add 90-135 mm | 36 kg | 140 kg |

SHIPPING SPECIFICATIONS

| Width (packed) | Depth (packed) | Height (packed) | Volume (packed) | Gross weight |
|----------------|----------------|-----------------|----------------------|--------------|
| 667 mm | 928 mm | 1,201 mm | 0.743 m ³ | 48 kg |

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

Please observe: Allow 10 mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and water connections).



HOSHIZAKI

Hoshizaki Middle East

sales.ex@hoshizaki-europe.com

www.hoshizaki-europe.com