



HOSHIZAKI

Advance F 140-4 C U

Double door freezer



PRODUCT SERIES: ADVANCE, ADVANCE 140

ITEM NUMBER: 133142090

COUNTRY OF ORIGIN: TURKEY

Hoshizaki Advance F 140 C U is a 2/1 GN deep double door freezer with a net usable volume of 797 ltr. ranking D in energy efficiency class. It has a cabinet height of 1975mm and depth of 830 mm.

- Ventilated refrigeration system
- Air circulation system
- Automatic fan cut-out when door is opened
- Automatic defrost with re-evaporation of defrost water
- Compartmentalized design for maximum internal capacity and easy maintenance
- Clean free condenser (condenser filter not needed)
- Heavy duty cabinet
- Climate class 5 cooling system enduring up to +40°C ambient temperature
- Exterior and interior of stainless steel AISI 304
- Anti-tilt shelf-supports moulded into the inner lining
- Complete wall rails, Shelf support
- Internal LED lighting
- Right hand hinged reversible door
- Automatic door closing
- Door lock
- Removable magnetic door gaskets
- Pan-shaped inside base with rounded corners to catch fluids
- IP2X water protection
- Matching design identity as the Advance counters



2 / 1 GN

ACCESSORIES INCLUDED

6 grey shelves (530 x 650mm) + 2 bottom shelves

OPTIONAL EXTRAS

Set of legs 130-180 mm

Set of castors 125 mm (2 x broken and 2 x unbroken)

Grey shelf with back guard

Grey bottom shelf with back guard

Stainless shelf with back guard

Stainless bottom shelf with back guard

Set of stainless shelves (6 top and 2 bottom) with back guard

Shelf support U-shape, left side

Shelf support U-shape, right side

Master key

Pedal door openers with overload protection

WARRANTY PERIOD

5 Years on Parts & Labour

EXTERIOR

Stainless Steel

INTERIOR

Stainless steel

Refrigerant type: R290 / Refrigerant: 0.105 kg / CO2 equivalent: 0.315 kg

CERTIFICATIONS



Energy consumption	Energy efficiency class	Energy efficiency class standard	Energy Efficiency Index (EEI)
3,642 kWh	D	ISO 22041-2019	67.44 EEI



HOSHIZAKI

Advance F 140-4 C U



TECHNICAL SPECIFICATIONS

Temperature range	Shelf size	Volume, gross	Volume, net	Power supply	Connection load	Climate class	Sound level	Ref. capacity - at -25°C
-25/-12°C	2/1 GN deep	1,200 l	797 l	230V, 50Hz	700 kW	5 (max. ambient 40°C w/ 40% RH)	56 dB	674 W


SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume (packed)	Gross weight	Width	Depth	Height	Net weight
1,435 mm	920 mm	2,090 mm	2.76 m ³	199 kg	1,344 mm	830 mm	1,975 mm	188 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.



A-A



B-B

LEG	CASTER



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands
Hoshizaki Norge
Hoshizaki Sverige
Hoshizaki UK
Export countries
Other countries

info@hoshizaki.nl
salg@hoshizaki.no
orderSE@hoshizaki.dk
uksales@hoshizaki.uk
sales.ex@hoshizaki-europe.com
sales.ex@hoshizaki-europe.com

www.hoshizaki.uk