

Baker SF 550 C DR U

Quick Chiller/Freezer



PRODUCT SERIES: BAKER 550
ITEM NUMBER: 147552030
COUNTRY OF ORIGIN: TURKEY

Hoshizaki BAKER SF 550 C DR U is a quick chiller/freezer that can also operate as a storage refrigerator/freezer and a controlled thawing cabinet. It is for tray slides 400 x 600mm, has a gross volume of 480 ltr. and a cabinet height of 2075mm.

- Operates as a quick chiller/freezer, storage refrigerator/freezer or as a controlled thawing cabinet.
- Air circulation system.
- Automatic fan cut out switch.
- Automatic defrost with re-evaporation of defrost water.
- Heavy duty cabinet and compressor compartment construction.
- Climate class 5 cooling system enduring up to +40°C ambient temperature.
- Exterior and interior of stainless steel AISI 304.
- Reversible and self closing door with lock.
- Removable magnetic door gaskets with triple insulation area.
- LED lighting.
- 25 sets of bakery tray supports.
- Pan-shaped inside base with rounded corners to catch fluids.
- Pedal door opener with overload protection.
- IP21 water protection.

ACCESSORIES INCLUDED

25 sets of bakery tray supports

OPTIONAL EXTRAS

Set of legs 130-180mm

Set of castors Ø100mm

Grey shelf 1/1 EN with back upstand

Stainless shelf 1/1 EN with back upstand

Set (4 of) of stainless shelves 1/1 EN with back upstand

Shelf supports (2 of)

Master key

WARRANTY PERIOD

6 Years on Parts & Labour

EXTERIOR

Stainless steel AISI 304

INTERIOR

Stainless steel AISI 304

Refrigerant type: R290 / GWP: 3 GWP / Refrigerant: 0.149 kg / CO2 equivalent: 0.447 kg

CERTIFICATIONS





HOSHIZAKI

Baker SF 550 C DR U


TECHNICAL SPECIFICATIONS

Bakery tray size (mm)	Bakery tray insertion	Quick chill capacity from +25°C to +3°C in 90 min	Quick freeze capacity from +25°C to -18°C in 120 min	Temperature range	Volume, gross	Power supply	Connection load	Climate class	Ref. capacity (at -30°C)
400 x 600	Longitudinal insertion	30 kg	10 kg	-30/+10°C	480 l	230V, 50Hz	680 W	5 (max. ambient 40°C w/ 40% RH)	882 W

SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume (packed)	Gross weight	Width	Depth	Height	Net weight
700 mm	980 mm	2,270 mm	1.56 m ³	140 kg	610 mm	895 mm	2,075 mm	124 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands
Hoshizaki Norge
Hoshizaki Sverige
Hoshizaki UK
Export countries
Other countries

info@hoshizaki.nl
salg@hoshizaki.no
order@hoshizaki.se
uksales@hoshizaki.uk
sales.ex@hoshizaki-europe.com
sales.ex@hoshizaki-europe.com

www.hoshizaki.uk