



HOSHIZAKI

PREMIER BCF RI U 200 CO2 1N DL

Roll-in Unibody Blast Chiller/Freezer for remote CO2 cooling system



COMPATIBLE WITH

Trolleys 2 x GN1/1, 1 x GN2/1 or 2 x EN60/40, 1 x EN60/80

ACCESSORIES INCLUDED

N/A

OPTIONAL EXTRAS

Bumpers *

Ozone generator *

Right-hand hinged door *

Wooden crate packaging *

* Add-on = Must be specified when placing the order

PRODUCT SERIES: ROLL-IN UNIBODY BLASTCHILLER/FREEZER

ITEM NUMBER: 5BMA8DCRH-40A3MC

COUNTRY OF ORIGIN: ITALY

PREMIER BCF RI U 200 CO2 1N DL is a HACCP compliant blast chiller/freezer applicable for trolley GN1/1, EN60/40 or GN2/1, EN60/80. Chilling/freezing capacity of 200/160kg.

The cabinet comes with floor, ramp, controller, wi-fi connection, Ethernet port, core probe, external condensate drain tube, USB-port and lock closure.

- 7" touch screen controller with coloured icons
- Chilling, freezing, preservation, precooling, ice cream hardening, fish sanitisation, bottle cooling, pastry, cell sanitisation, thawing, cell drying
- Choice of time- or temperature-controlled (probe) chill/freeze cycles
- Single probe cascade cycles, Timer cycles, Quick start
- Heated core probe
- Can be connected to wi-fi
- Ethernet port
- USB-port for HACCP data collection
- Customisable parameters
- Multiple and customisable cycle stages
- Adjustable fan speed
- Operating in ambient temperatures up to +40°C
- Hot gas defrosting
- Front access to electrical box
- Internal fan section can be opened for easy cleaning around and behind
- Left-hand hinged door (right-hand hinged door is optional)
- Heated door perimeter
- Built-in flush-mounted trolley ramp
- Evaporator with cataphoresis coating for rust protection
- Rounded internal corners
- Lock closure

WARRANTY PERIOD

1 Year on Parts & Labour

EXTERIOR

Stainless steel AISI 304

INTERIOR

Stainless steel AISI 304

Refrigerant: 3 x 0.15kg / Refrigerant compatibility: R744



HOSHIZAKI

PREMIER BCF RI U 200 CO2 1N DL

TECHNICAL SPECIFICATIONS

Cooling system	Temperature range	Power supply	Required cooling capacity	Connection load	Fuse Rating	Chilling capacity (from +70°C to +3°C in 90 minutes)	Freezing capacity (from +70°C to -18°C in 4 hours)
For remote cooling system	-40/+40°C	380-420V/1N/50Hz	17,977 W	573 W	16 A	200 kg	160 kg

Climate class	Net weight	Door clear opening (W x H)	Dimensions internal (W x D x H)	Dimensions external (W x D x H)
5 (max. ambient 40°C w/ 40% RH)	340 kg	858 x 1881,8 mm	870 mm x 957 mm x 1,881 mm	1,390 mm x 1,221 mm x 2,223 mm

SHIPPING SPECIFICATIONS

Dimensions packed (W x D x H)	Volume (packed)	Gross weight
1,250 mm x 1,450 mm x 2,400 mm	4.4 m ³	370 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige order@hoshizaki.se
Hoshizaki UK uksales@hoshizaki.uk
Export countries sales.ex@hoshizaki-europe.com
Other countries sales.ex@hoshizaki-europe.com

www.hoshizaki.uk

PREMIER BCF RI U 200 CO2 1N DL

