

# ACF-180DG-LRR-RRC-C1 U

# **3-Section Freezer Counter**





# 1/1 GN

## **ACCESSORIES INCLUDED**

2 grey shelves per door section

## **OPTIONAL EXTRAS**

Set of legs 130-180mm (L1) Set of legs 135-200mm (L2)

Set of 4 Castors for 900mm Counter-top (C2)

Castor Extension Kit (extends height of castors by 50mm)

Flat worktop with 100mm splashback

Shelf support - Left Shelf support - Right Stainless shelf

Grey shelf

 Energy consumption
 Energy efficiency class
 Energy efficiency class standard
 Energy Efficiency Index (EEI)

 2,892 kWh/year
 D
 ISO 22041-2019
 74.53 EEI

PRODUCT SERIES: ADVANCE ITEM NUMBER: 899020861 COUNTRY OF ORIGIN: TURKEY

Hoshizaki Advance ACF-180DG-LRR-RRC-C1 U is a 3-section 1/1 GN freezer counter with three doors and a flat worktop. It has a net usable volume of 257 ltr. The height excluding castors is 700mm, castors = H 150mm (C1). Shelf width is 325mm.

- Fan assisted cooling
- Automatic defrost with re-evaporation of defrost water
- Heavy duty cabinet and compressor compartment construction
- Climate class 5 cooling system enduring up to +40°C ambient temperature
- Exterior and interior of stainless steel
- Compartmentalized cooling unit that is available as one unit
- A compact slide out refrigeration unit for maintenance and service
- Removable condenser filter for cleaning or replacement
- Reversible doors
- · Anti-tilt shelves
- Removable magnetic door gaskets with triple insulation area
- Pan-shaped inside base with rounded corners to catch fluids
- IP 21 water protection
- Matching design identity as the Advance cabinets

WARRANTY PERIOD

5 Years on Parts & Labour

EXTERIOR
Stainless Steel

INTERIOR
Stainless steel

Refrigerant type: R290 / Refrigerant: 0.06 kg / CO2 equivalent: 0.18 kg  $\,$ 

### **CERTIFICATIONS**









# ACF-180DG-LRR-RRC-C1 U


### **TECHNICAL SPECIFICATIONS**

Temperature range	Shelf size	Volume, gross	Net usable volume	Power supply	Connection load	Climate class	Ref. capacity - at -30°C
-22/-5°C	1/1 GN	457	257	230V, 50Hz	639 W	5 (max. ambient 40°C w/ 40% RH)	506 W

### SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume (packed)	Gross weight	Width	Depth	Height	Net weight
1,870 mm	820 mm	950 mm	1.46 m3	140 kg	1,780 mm	700 mm	850 mm	128 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.





Hoshizaki Belgium Hoshizaki Danmark Hoshizaki Deutschland Hoshizaki France Hoshizaki Iberia Hoshizaki Italia Hoshizaki Middle East info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands Hoshizaki Norge Hoshizaki Sverige Hoshizaki UK Export countries Other countries info@hoshizaki.nl
salg@hoshizaki.no
orderSE@hoshizaki.dk
uksales@hoshizaki.uk
sales.ex@hoshizaki.europe.com
sales.ex@hoshizaki.europe.com