

## ACF-225DG-LLRR-RRC-C1 U

### 4-Section Freezer Counter



PRODUCT SERIES: ADVANCE  
ITEM NUMBER: 899040861  
COUNTRY OF ORIGIN: TURKEY

Hoshizaki Advance ACF-225DG-LLRR-RRC-C1 U is a 4-section 1/1 GN freezer counter with four doors and a flat worktop. It has a net usable volume of 343 litr. The height excluding castors is 700mm, castors = H 150mm (C1). Shelf width is 325mm.

- Fan assisted cooling
- Automatic defrost with re-evaporation of defrost water
- Heavy duty cabinet and compressor compartment construction
- Climate class 5 cooling system enduring up to +40°C ambient temperature
- Exterior and interior of stainless steel
- Compartmentalized cooling unit that is available as one unit
- A compact slide out refrigeration unit for maintenance and service
- Removable condenser filter for cleaning or replacement
- Reversible doors
- Anti-tilt shelves
- Removable magnetic door gaskets with triple insulation area
- Pan-shaped inside base with rounded corners to catch fluids
- IP 21 water protection
- Matching design identity as the Advance cabinets



1 / 1 GN

#### ACCESSORIES INCLUDED

2 grey shelves per door section

#### OPTIONAL EXTRAS

Set of legs 130-180mm (L1)  
Set of legs 135-200mm (L2)  
Set of 4 Castors for 900mm Counter-top (C2)  
Castor Extension Kit (extends height of castors by 50mm)  
Flat worktop with 100mm splashback  
Shelf support - Left  
Shelf support - Right  
Stainless shelf  
Grey shelf

#### WARRANTY PERIOD

**5 Years on Parts & Labour**

#### EXTERIOR

**Stainless Steel**

#### INTERIOR

**Stainless steel**

Refrigerant type: R290 / Refrigerant: 0.072 kg / CO2 equivalent: 0.216 kg

#### CERTIFICATIONS



Energy consumption	Energy efficiency class	Energy efficiency class standard	Energy Efficiency Index (EEI)
3,278 kWh/year	D	ISO 22041-2019	74.79 EEI



# HOSHIZAKI

## ACF-225DG-LLRR-RRC-C1 U

### TECHNICAL SPECIFICATIONS

Temperature range	Shelf size	Volume, gross	Net usable volume	Power supply	Connection load	Climate class	Ref. capacity - at -30°C
-22/-5°C	1/1 GN	625 l	343 l	230V, 50Hz	752 W	5 (max. ambient 40°C w/ 40% RH)	608 W

### SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume (packed)	Gross weight	Width	Depth	Height	Net weight
2,335 mm	820 mm	950 mm	1.82 m3	178 kg	2,246 mm	700 mm	850 mm	159 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

