



HOSHIZAKI

COMPACT KG 220 RG 2W UNDERCOUNTER GLASS DOOR REFRIGERATOR



PRODUCT SERIES: GRAM COMPACT 220
ITEM NUMBER: 962210441

COMPACT KG 220 models not only comply with the EU Ecodesign labelling regulation, but ranking in energy efficiency class B makes these glass door refrigerators the most energy efficient compact models in the marketplace. Correct and uniform temperature throughout the cabinet is critically important for a food storage cabinet. GRAM COMPACT provides this with a unique ventilated air distribution system and a robust refrigeration system with sufficient refrigeration capacity. It also has approximately 70% more insulation than a bottle cooler. COMPACT glass door refrigerators are display cabinets with LED lighting built into the glass door. It is approved to endure up to 30°C ambient temperature (climate class 4).

COMPACT 220 models are designed to fit under worktops in commercial workplaces. With their width of 59.5cm, depth of 66.7 cm and height of just 83cm, these cabinets are ideal for building in beneath worktops. As a free-standing cabinet the undercounter COMPACT 220 provides extra work space with its "table top".

Materials Exterior: StainlessMaterials Interior: White polystyrene (PS) lining. Gross volume: 128 ltr

- Air circulation system
- Right hand hinged door
- Integrated full height door handle.
- Internal LED light
- 2 anti tilt white shelves
- Door lock for extra security
- Automatic defrost with re-evaporation of defrost water
- Low sound level of just 33.7 dB(A)
- Hydrocarbon refrigerant
- 10 year spare parts availability guaranteed

WARRANTY PERIOD

5 Years on Parts & Labour

EXTERIOR

Stainless Steel

Refrigerant type: R600a / Refrigerant: 0.031 kg / CO2 equivalent: 0.09 kg

Energy efficiency class	Energy Efficiency Index (EEI)
B	27.3 EEI



HOSHIZAKI

COMPACT KG 220 RG 2W

TECHNICAL SPECIFICATIONS

Temperature range	Shelf size	Volume, gross	Net usable volume	Volume, net	Power supply	Climate class	Sound level	Ref. capacity (at -10°C)
+2/+12°C	Shelf 484.7 x 433 mm	123 l	77 l	77 l	230V, 50Hz	4 (max. ambient temp. of 30 °C with 55% RH)	33.7 dB(A)	159 W

SHIPPING SPECIFICATIONS

Gross weight	Width	Depth	Height	Net weight
58 kg	595 mm	667 mm	833 mm	58 kg



Dimensional drawing coming soon



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige order@hoshizaki.se
Hoshizaki UK uksales@hoshizaki.uk
Export countries sales.ex@hoshizaki-europe.com
Other countries sales.ex@hoshizaki-europe.com

www.hoshizaki.uk