HOSHIZAKI

Premier U 70 DR U Ru1

Refrigerator/Freezer 'U' type with RU1 valve for remote cooling system

GAMMA DE PRODUCTOS: PREMIER 70
NÚMERO DE ARTÍCULO: 188701031

2/1 GN

Hoshizaki Premier U 70 DR U Ru1 is a 2/1 GN deep cabinet with RU1 valve for connection to a remote cooling system. It is ready to install and is compatible with multiple refrigerants. This heavy duty cabinet has a gross volume of 700 ltr. and the height of the cabinet with adjustable legs is 2080-2130mm. Adjustable legs are 130-180mm. The depth is 848 mm without pedal door opener (920 mm incl. pedal door opener).

Ultimate flexibility with 'U' type cabinet:
The cabinet can be set to run as a refrigerator or as a freezer. Set the controller to run as either K, M or F cabinet with the following temperature ranges:

K: +2/+12°C M: -5/+12°C F: -25/-5°C

- Ready-to-install cabinet with RU1 valve
- Air distribution system
- Automatic fan cut-out when door is opened
- Automatic electric defrost with re-evaporation of defrost water
- Heavy duty cabinet
- Tested to climate class 5
- Exterior and interior of stainless steel AISI 304
- Anti-tilt shelf supports moulded into the inner lining
- LED lighting on the top panel
- Right hand hinged reversible door
- Automatic door closing
- Door lock
- Removable magnetic door gaskets
- Pedal door opener with overload protection (included as accessory)
- Pan-shaped inside base with rounded corners to catch fluids
- Low sound level
- IP21 water protection
- Matching design identity as the Premier counters

ACCESORIOS INCLUIDOS

3 estantes grises (530 x 650mm) + 1 inferior, Apertura de puerta con pedal y protección contra sobrecarga

EXTRAS OPCIONALES

Grey shelf with back guard
Grey bottom shelf with back guard
Stainless shelf with back guard
Stainless bottom shelf with back guard
Set of stainless shelves (3 top and 1 bottom) with back guard
Master key

PERÍODO DE GARANTÍA	EXTERIOR
6 años en piezas y mano de obra	**Acero inoxidable AISI 304**

INTERIOR
Acero inoxidable AISI 304

Compatibilidad de refrigerante: R448A, R449A, R455A

CERTIFICACIONES

ISO HOSHIZAKI • ISO 9001 ISO HOSHIZAKI • ISO 14001 CE

Hoshizaki Iberia
Travessera de Gràcia, 73-79 4t 6ª
08006 Barcelona
España

T. +34 (0)93 626 03 17
info@hoshizaki.es
www.hoshizaki.es

Premier U 70 DR U Ru1

ESPECIFICACIONES TÉCNICAS

Min. cooling capacity	Tamaño del estante	Volumen bruto	Fuente de alimentación	Temperature Range Span	Clase climática
300 W	Profundidad de 2/1 GN	700 l	230V, 50Hz	-25/+12°C	5

ESPECIFICACIONES DE ENVÍO

Ancho (en caja)	Profundo (en caja)	Altura (en caja)	Volumen (en caja)	Peso bruto	Ancho	Profundo	Altura incluyendo piernas (mínimo)	Altura incluyendo patas (máximo)	Peso neto
750 mm	975 mm	2.150 mm	1,572 m3	115 kg	690 mm	848 mm	2.080 mm	2.130 mm	105 kg

Descargo de responsabilidad: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.



HOSHIZAKI

Hoshizaki Belgium info@hoshizaki.nl
Hoshizaki Danmark info@hoshizaki.dk
Hoshizaki Deutschland vertrieb@hoshizaki.de
Hoshizaki France info@hoshizaki.fr
Hoshizaki Iberia info@hoshizaki.es
Hoshizaki Italia commerciale@hoshizaki.it
Hoshizaki Middle East sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige orderSE@hoshizaki.dk
Hoshizaki UK uksales@hoshizaki.uk
Países exportadores sales.ex@hoshizaki-europe.com
Otros paises sales.ex@hoshizaki-europe.com

www.hoshizaki.es