SUR-65EG-C-L

Refrigerador, una puerta

NÚMERO DE ARTÍCULO: 877000900

La gama Snowflake GII Refrigeration está diseñada para trabajar en entornos exigentes, ofreciendo una gran tranquilidad al usuario. Con un inteligente diseño tanto interior como exterior, nuestros armarios y mesas refrigeradasofrecen una refrigeración de calidad para sus productos frescos.

SustainableThe refrigerant used in all Snowflake GII+ models is R290. This agent is a natural gas that enhances the performance of the refrigerated counter and has, compared to other refrigerants, a minimal ozone depletion potential. MaterialBoth interior and exterior of the refrigerated cabinet are built of nickel-free (non-allergic) stainless steel, which is among the best choices for hygienic and food-safe cooking environments.Smart Use of SpaceMaking the best possible use of limited space conditions is a common challenge in kitchen design. The evaporator is positioned on top of the cabinet, so valuable space inside the cabinet can be used for storage. The condensation tray is not positioned on the back of the cabinet, but on top of it. This clever design allows you to move the cabinet closer to the back wall which gives you an additional 5 cm of your valuable operational area. Energy EfficiencyThe double insulated and extra wide door gaskets help to keep the cold air inside the cabinet, which is an important factor for device efficiency. The Ecodesign AEC Energy consumption is 548. Convenience and ErgonomicsThe SUR-65EG-C-L has self-closing doors, which close automatically when open in an angle of less than 90 degrees. Additionally, they offer maximum flexibility as they are fully reversible. an anti-tilt mechanism with moulded liners helps with safer container and rooster handling. The GN shelf size of the SUR-65EG-C-L is [2_1_gn_deep]. With sound levels of 54.0000 dB(A) the SUR-65EG-C-L adds to a comfortable work environment for your staff. Easy Cleaning & MaintenanceThe Snowflake GII+ refrigeration system uses a mono-block construction that is removable for easier maintenance and repair. The removable gaskets make sure that can clean the device thoroughly. This and other thoughtful extras, such as the cleaning-free condenser, are designed to reduce kitchen cleaning times whilst storing foods protectively in the best possible way.











EXTERIOR
Acero inoxidable AISI 304

INTERIOR
Acero inoxidable AISI 304

Tipo de refrigerante: R290 / Refrigerante: 0,058 kg / Equivalente de CO2: 0,174 kg

Consumo eléctrico	Clase de eficiencia energética	Índice de Eficiencia Energética (EEI)
548 kWh	C	42,41 EEI

Hoshizaki Iberia
Travessera de Gràcia, 73-79 4t 6ª
08006 Barcelona
España

T. +34 (0)93 626 03 17
info@hoshizaki.es
www.hoshizaki.es

SUR-65EG-C-L

ESPECIFICACIONES TÉCNICAS

Rango de temperatura	Tamaño del estante	Volumen bruto	Volumen neto utilizable	Fuente de alimentación	Carga de conexión	Clase climática	Nivel de sonido	Potencia frigorífica (a -10°C)
0/+10°C	Profundidad de 2/1 GN	600 l	415 l	230V, 50Hz	425 kW	5	54 dB(A)	297 kW

ESPECIFICACIONES DE ENVÍO

Peso bruto	Ancho	Profundo	Altura incluyendo piernas (mínimo)	Altura incluyendo patas (máximo)	Peso neto
122 kg	654 mm	830 mm	1.980 mm	2.030 mm	122 kg



Próximamente dibujo dimensional

Hoshizaki Belgium info@hoshizaki.nl
Hoshizaki Danmark info@hoshizaki.dk
Hoshizaki Deutschland vertrieb@hoshizaki.de
Hoshizaki France info@hoshizaki.fr
Hoshizaki Iberia info@hoshizaki.es
Hoshizaki Italia commerciale@hoshizaki.it
Hoshizaki Middle East sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige order@hoshizaki.se
Hoshizaki UK uksales@hoshizaki.uk
Países exportadores sales.ex@hoshizaki-europe.com
Otros paises sales.ex@hoshizaki-europe.com

www.hoshizaki.es