

SUR-135EG-C-C

Refrigerador, dos puertas



NÚMERO DE ARTÍCULO: 878000901

La gama Snowflake GII Refrigeration está diseñada para trabajar en entornos exigentes, ofreciendo una gran tranquilidad al usuario. Con un inteligente diseño tanto interior como exterior, nuestros armarios y mesas refrigeradas ofrecen una refrigeración de calidad para sus productos frescos.

Sustainable The refrigerant used in all Snowflake GII+ models is R290. This agent is a natural gas that enhances the performance of the refrigerated counter and has, compared to other refrigerants, a minimal ozone depletion potential. **Material** Both interior and exterior of the refrigerated cabinet are built of stainless steel AISI 304/ nickel-free (non-allergic) stainless steel AISI 430, which is among the best choices for hygienic and food-safe cooking environments. **Smart Use of Space** Making the best possible use of limited space conditions is a common challenge in kitchen design. The evaporator is positioned on top of the cabinet, so valuable space inside the cabinet can be used for storage. The condensation tray is not positioned on the back of the cabinet, but on top of it. This clever design allows you to move the cabinet closer to the back wall which gives you an additional 5 cm of your valuable operational area. **Energy Efficiency** The double insulated and extra wide door gaskets help to keep the cold air inside the cabinet, which is an important factor for device efficiency. The **Ecodesign AEC** Energy consumption is 926. **Convenience and Ergonomics** The SUR-135EG-C-C has self-closing doors, which close automatically when open at an angle of fewer than 90 degrees. Additionally, they offer maximum flexibility as they are fully reversible. an anti-tilt mechanism with moulded liners helps with safer container and rooster handling. The GN shelf size of the SUR-135EG-C-C is GN 2/1 deep. With sound levels of 53 dB(A), the SUR-135EG-C-C adds to a comfortable work environment for your staff. **Easy Cleaning & Maintenance** The Snowflake GII+ refrigeration system uses a mono-block construction that is removable for easier maintenance and repair. The removable gaskets make sure that can clean the device thoroughly. This and other thoughtful extras, such as the cleaning-free condenser, are designed to reduce kitchen cleaning times whilst storing foods protectively in the best possible way.

EXTERIOR

Acero inoxidable

INTERIOR

Inoxidable

Tipo de refrigerante: R290 / Refrigerante: 0,085 kg / Equivalente de CO2: 0,255 kg

Consumo eléctrico	Clase de eficiencia energética	Índice de Eficiencia Energética (EEI)
926 kWh	C	38,16 EEI



HOSHIZAKI

SUR-135EG-C-C

ESPECIFICACIONES TÉCNICAS

Rango de temperatura	Tamaño del estante	Volumen bruto	Volumen neto utilizable	Volumen neto	Fuente de alimentación	Carga de conexión	Clase climática	Nivel de sonido	Potencia frigorífica - a -10°C
0/+10°C	Profundidad de 2/1 GN	1.200 l	797 l	797 l	230V, 50Hz	250 kW	5	53 dB	632 kW

ESPECIFICACIONES DE ENVÍO

Peso bruto	Ancho	Profundo	Altura	Peso neto
192 kg	1.344 mm	830 mm	1.977 mm	192 kg



Próximamente dibujo dimensional



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige orderSE@hoshizaki.dk
Hoshizaki UK uksales@hoshizaki.uk
Países exportadores sales.ex@hoshizaki-europe.com
Otros países sales.ex@hoshizaki-europe.com

www.hoshizaki.es