



HOSHIZAKI

SUF-135EG-R-C-U

Congelador, una puerta



NÚMERO DE ARTÍCULO: 878010904

La gama Snowflake GII Refrigeration está diseñada para trabajar en entornos exigentes, ofreciendo una gran tranquilidad al usuario. Con un inteligente diseño tanto interior como exterior, nuestros armarios y mesas refrigeradas ofrecen una refrigeración de calidad para sus productos frescos.

As a product that is designed and built to last, this freezer cabinet combines an innovative design concept, premium materials and clever extras:

- Minimum cool air lost: double insulated and extra wide door gaskets help to keep the cold air into the cabinet
- Both interior and exterior are built of stainless steel which is among the best choices for hygienic and food safe cooking environments.
- Anti-tilt mechanism: moulded liners for safer container and rooster handling
- This and other thoughtful extras, such as the cleaning-free condenser, are designed to reduce kitchen cleaning times whilst storing foods protectively in the best possible way

The refrigerant used in all Snowflake GII HC models is R290. This agent is a natural gas which enhances the performance of the refrigerated counter and has, compared to other refrigerants, a minimal ozone depletion potential. R290 is one of the view refrigerants compliant with the called F-Gas Regulation, issued by the European Commission. This regulation aims to phase out HFCs (Hydrofluorocarbons) as of 2020 to make space for eco-friendlier alternatives and substances, such as HCs (Hydrocarbon) and find more information about the F-Gas regulation here.

EXTERIOR

Acero inoxidable

INTERIOR

Inoxidable

Tipo de refrigerante: R290 / Refrigerante: 0,105 kg / Equivalente de CO2: 0,315 kg

Clase de eficiencia energética	Índice de Eficiencia Energética (EEI)
D	71,66 EEI



HOSHIZAKI

SUF-135EG-R-C-U

ESPECIFICACIONES TÉCNICAS

Rango de temperatura	Tamaño del estante	Volumen bruto	Volumen neto utilizable	Volumen neto	Fuente de alimentación	Clase climática	Nivel de sonido	Potencia frigorífica (a -25°C)
-22/-5°C	Profundidad de 2/1 GN	1.200 l	797 l	797 l	230V, 50Hz	5	58 dB	673 W

ESPECIFICACIONES DE ENVÍO

Peso bruto	Ancho	Profundo	Altura	Peso neto
198 kg	1.344 mm	830 mm	1.977 mm	198 kg



Próximamente dibujo dimensional



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige orderSE@hoshizaki.dk
Hoshizaki UK uksales@hoshizaki.uk
Países exportadores sales.ex@hoshizaki-europe.com
Otros países sales.ex@hoshizaki-europe.com

www.hoshizaki.es