

SCR-180DG-LRR-RRC-C1 U

mesa refrigerada, tres secciones



GAMMA DE PRODUCTOS: SNOWFLAKE SCR
NÚMERO DE ARTÍCULO: 879020861

La gama Snowflake GII Refrigeration está diseñada para trabajar en entornos exigentes, ofreciendo una gran tranquilidad al usuario. Con un inteligente diseño tanto interior como exterior, nuestros armarios y mesas refrigeradas ofrecen una refrigeración de calidad para sus productos frescos.

As a product that is designed and built to last, this refrigerated counter combines an innovative design concept, premium materials and clever extras:

- Minimum cool air lost: double insulated and extra wide door gaskets help to keep the cold air into the cabinet
- Both interior and exterior are built of stainless steel which is among the best choices for hygienic and food safe cooking environments
- Anti-tilt mechanism: extra-long drawers with u-shaped, telescopic rails
- Multiple door-drawer combinations possible
- Removable gaskets make sure you can clean the device thoroughly
- This and other thoughtful extras, such as the cleaning-free condenser, are designed to reduce kitchen cleaning times whilst storing foods protectively in the best possible way

The refrigerant used in all Snowflake GII HC models is R290. This agent is a natural gas which enhances the performance of the refrigerated counter and has, compared to other refrigerants, a minimal ozone depletion potential. R290 is one of the view refrigerants compliant with the called F-Gas Regulation, issued by the European Commission. This regulation aims to phase out HFCs (Hydrofluorocarbons) as of 2020 to make space for eco-friendlier alternatives and substances, such as HCs (Hydrocarbon) and find more information about the F-Gas regulation here.

EXTERIOR
Acero inoxidable

INTERIOR
Inoxidable

Tipo de refrigerante: R290 / Equivalente de CO2: 0,237 kg

Clase de eficiencia energética

C



HOSHIZAKI

SCR-180DG-LRR-RRC-C1 U

ESPECIFICACIONES TÉCNICAS

Rango de temperatura	Tamaño del estante	Volumen bruto	Volumen neto	Fuente de alimentación	Clase climática
-2/+8°C	1/1 GN	500 l	257 l	230V, 50Hz	5

ESPECIFICACIONES DE ENVÍO

Peso bruto	Ancho	Profundo	Altura	Peso neto
141 kg	1.780 mm	700 mm	856 mm	141 kg



Próximamente dibujo dimensional



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige orderSE@hoshizaki.dk
Hoshizaki UK uksales@hoshizaki.uk
Países exportadores sales.ex@hoshizaki-europe.com
Otros países sales.ex@hoshizaki-europe.com

www.hoshizaki.es