

## BAKER STANDARD F 69 LFG C1 15B



GAMMA DE PRODUCTOS: GRAM BAKER STANDARD 69  
NÚMERO DE ARTÍCULO: 960690298

BAKER STANDARD F 69 FFG has a stainless interior and exterior, EN1.4016 / AISI 430.

The cabinet is on legs, total height including castors is 2100 mm.

Equipped with right hand hinged door with lock, automatic door closing, LED light, 15 pairs of adjustable trayslides, castors C1 height 110 mm.

Pedal door opener is available as optional extra and will be supplied with the cabinet (not factory fitted). Likewise the cabinet can be fitted with additional bakery plates.

BAKER STANDARD offers the following HACCP functionalities and features: Open door alarm High temperature alarm Duration of alarm period Highest critical temperature Reset alarm & period Easy to clean surfaces and handle 15 sets of trayslides, number of levels is 53, distance between levels is 25 mm

Optional with legs L2 height 135 - 200 mm. Supports for plates 400 x 600 mm.

**PERÍODO DE GARANTÍA**  
**5 años en piezas y mano de obra**

**EXTERIOR**  
**Blanco**

**INTERIOR**  
**Inoxidable**

Tipo de refrigerante: R290 / Refrigerante: 0,08 kg / Equivalente de CO2: 0,225 kg

| Clase de eficiencia energética | Índice de Eficiencia Energética (EEI) |
|--------------------------------|---------------------------------------|
| D                              | 61,3 EEI                              |



# HOSHIZAKI

## BAKER STANDARD F 69 LFG C1 15B

### ESPECIFICACIONES TÉCNICAS

| Rango de temperatura | Volumen bruto | Volumen neto utilizable | Volumen neto | Fuente de alimentación | Nivel de sonido | Potencia frigorífica - a -25°C |
|----------------------|---------------|-------------------------|--------------|------------------------|-----------------|--------------------------------|
| -25/-5°C             | 610 l         | 342 l                   | 342 l        | 230V, 50Hz             | 44,5 dB         | 339 W                          |

### ESPECIFICACIONES DE ENVÍO

| Peso bruto | Ancho  | Profundo | Altura   | Peso neto |
|------------|--------|----------|----------|-----------|
| 136 kg     | 700 mm | 895 mm   | 2.100 mm | 136 kg    |



Próximamente dibujo dimensional



# HOSHIZAKI

Hoshizaki Belgium  
Hoshizaki Danmark  
Hoshizaki Deutschland  
Hoshizaki France  
Hoshizaki Iberia  
Hoshizaki Italia  
Hoshizaki Middle East

[info@hoshizaki.nl](mailto:info@hoshizaki.nl)  
[info@hoshizaki.dk](mailto:info@hoshizaki.dk)  
[vertrieb@hoshizaki.de](mailto:vertrieb@hoshizaki.de)  
[info@hoshizaki.fr](mailto:info@hoshizaki.fr)  
[info@hoshizaki.es](mailto:info@hoshizaki.es)  
[commerciale@hoshizaki.it](mailto:commerciale@hoshizaki.it)  
[sales.ex@hoshizaki-europe.com](mailto:sales.ex@hoshizaki-europe.com)

Hoshizaki Netherlands [info@hoshizaki.nl](mailto:info@hoshizaki.nl)  
Hoshizaki Norge [salg@hoshizaki.no](mailto:salg@hoshizaki.no)  
Hoshizaki Sverige [orderSE@hoshizaki.dk](mailto:orderSE@hoshizaki.dk)  
Hoshizaki UK [uksales@hoshizaki.uk](mailto:uksales@hoshizaki.uk)  
Países exportadores [sales.ex@hoshizaki-europe.com](mailto:sales.ex@hoshizaki-europe.com)  
Otros países [sales.ex@hoshizaki-europe.com](mailto:sales.ex@hoshizaki-europe.com)

[www.hoshizaki.es](http://www.hoshizaki.es)