



HOSHIZAKI

SCR-180DG-LRR-RRC-L2 3-Section Refrigerated Counter, HC

SERIE: SNOWFLAKE SCR
CODICE ARTICOLO: 879020842

The Snowflake GII series is brought to you by Japanese and Danish engineering excellence, dedicated to simplifying the day-to-day work routines of kitchen staffs all around the world.

The technology behind the performance boost of Snowflake GII is the tropicalised cooling system enduring up to +40°C. Additionally, the cooling agent of the new generation of Snowflake is the eco-friendly refrigerant R290, a natural gas (HC) that enhances the performance and cuts down energy consumption significantly.

Both interior and exterior are built of anti-corrosion stainless steel, which is among the best choices for hygienic and food safe cooking environments.

The Snowflake GII SCR-180DG-LRR-RRC-L1 is a 3-section refrigerated counter with a net internal volume of 257 Ltr.

As a product that is designed and built to last, this refrigerated counter combines an innovative design concept, premium materials and clever extras:

- Minimum cool air lost: double insulated and extra wide door gaskets help to keep the cold air into the cabinet
- Both interior and exterior are built of stainless steel which is among the best choices for hygienic and food safe cooking environment
- Anti-tilt mechanism: extra-long drawers with u-shaped, telescopic rails
- Multiple door-drawer combinations possible
- Removable gaskets make sure you can clean the device thoroughly
- This and other thoughtful extras, such as the cleaning-free condenser, are designed to reduce kitchen cleaning times whilst storing foods protectively in the best possible way

The refrigerant used in all Snowflake GII HC models is R290. This agent is a

RIVESTIMENTO ESTERNO
Acciaio Inox

RIVESTIMENTO INTERNO
Acciaio Inox

Tipologia refrigerante: R290 / Equivalente CO2: 0,237 kg

Classe di efficienza energetica

C



HOSHIZAKI

SCR-180DG-LRR-RRC-L2

SPECIFICHE TECNICHE

Intervallo di temperatura	Dimensioni ripiano	Volume lordo	Volume netto	Alimentazione	Classe climatica
-2/+8°C	1/1 GN prof.	500 l	257 l	230V, 50Hz	5

SPECIFICHE DI TRASPORTO

Peso lordo	Larghezza	Profondità	Altezza inclusa le gambe (minimo)	Altezza inclusi le gambe (massimo)	Peso netto
141 kg	1.780 mm	700 mm	835 mm	900 mm	141 kg



Presto il disegno dimensionale



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige orderSE@hoshizaki.dk
Hoshizaki UK uksales@hoshizaki.uk
Paesi di esportazione sales.ex@hoshizaki-europe.com
Altri paesi sales.ex@hoshizaki-europe.com

www.hoshizaki-europe.com