



HOSHIZAKI

SUR-65EG-C-L

1-Door Refrigerated Cabinet 2/1 GN



NUMER ARTYKUŁU: 877000900

The Hoshizaki SUR-65EG-C-L is a 1-Door Refrigerated Cabinet 2/1 GN with a net internal volume of 415 Ltr.

As a product that is designed and built to last, this refrigerated cabinet combines an innovative design concept, premium materials, and clever extras.

The technology behind the strong performance of the Snowflake GII+ series is the tropicalised cooling system, enduring up to +40°C.

With outside dimensions W x D x H of mm, the SUR-65EG-C-L makes a perfect fit for diverse food service environments, especially for locations with low ceilings.

The SUR-65EG-C-L is also easy to maneuver through door openings, which simplifies the process of installation.

The Hoshizaki Snowflake GII+ series is brought to you by Japanese and Danish engineering excellence, dedicated to simplifying the day-to-day work routines of kitchen staff all around the world.

Sustainable The refrigerant used in all Snowflake GII+ models is R290. This agent is a natural gas that enhances the performance of the refrigerated counter and has, compared to other refrigerants, a minimal ozone depletion potential.

Material Both interior and exterior of the refrigerated cabinet are built of nickel-free (non-allergic) stainless steel, which is among the best choices for hygienic and food-safe cooking environments.

Smart Use of Space Making the best possible use of limited space conditions is a common challenge in kitchen design. The evaporator is positioned on top of the cabinet, so valuable space inside the cabinet can be used for storage.

The condensation tray is not positioned on the back of the cabinet, but on top of it. This clever design allows you to move the cabinet closer to the back wall which gives you an additional 5 cm of your valuable operational area.

Energy Efficiency The double insulated and extra wide door gaskets help to keep the cold air inside the cabinet, which is an important factor for device efficiency. The Ecodesign AEC Energy consumption is 548.

Convenience and Ergonomics The SUR-65EG-C-L has self-closing doors, which close automatically when open in an angle of less than 90 degrees.

Additionally, they offer maximum flexibility as they are fully reversible. an anti-tilt mechanism with moulded liners helps with safer container and rooster handling. The GN shelf size of the SUR-65EG-C-L is [2_1_gn_deep]. With sound levels of 54.0000 dB(A) the SUR-65EG-C-L adds to a comfortable work environment for staff.



OBUDOWA

Stal nierdzewna AISI 304

WNĘTRZE

Stal nierdzewna AISI 304

best possible way.

Rodzaj czynnika chłodniczego: R290 / Czynnik chłodniczy: 0,058 kg /
Ekwiwalent CO2: 0,174 kg

Zużycie energii	Klasa energooszczędności	Indeks efektywności energetycznej (EEI)
548 kWh	C	42,41 EEI



HOSHIZAKI

SUR-65EG-C-L

SPECYFIKACJA TECHNICZNA

Zakres temperatur	Rozmiar prusztu	Objętość, brutto	Objętość powierzchni netto	Objętość, netto	Zasilanie	Obciążenie przyłącza	Klasa klimatyczna	Poziom głośności	Wydajność (w -10°C)
0/+10°C	2/1 GN głęboki	600 l	415 l	415 l	230V, 50Hz	425 kW	5	54 dB	297 kW

SPECYFIKACJA WYSYŁKI

Waga brutto	Szerokość	Głębokość	Wysokość z nogami (minimalna)	Wysokość łącznie z nogami (maksimum)	Waga netto
122 kg	654 mm	830 mm	1 980 mm	2 030 mm	122 kg



Dimensional drawing coming soon



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige orderSE@hoshizaki.dk
Hoshizaki UK uksales@hoshizaki.uk
Export countries sales.ex@hoshizaki-europe.com
Other countries sales.ex@hoshizaki-europe.com

www.hoshizaki-europe.com