



HOSHIZAKI

BEERMATIC DualTap DBF-AS65WE-EU Beer Dispenser



NUMER ARTYKUŁU: B078-D011
MARKA: HOSHIZAKI

The HOSHIZAKI BEERMATIC DUAL TAP is a fully automatic Draft Beer Dispenser with foaming mechanism. This counter top model has two separate circuits. This means two different types of beer can be served at the same time. The hands-free portion control allows a pre-set quantity of chilled draft beer and foam to be served at the push of a button. This dispenser is great for cafes, restaurants, pubs, temporary bars, outdoor beer gardens, event venues, event catering, vending opportunities.

Perfect portioning: The beer -to-foam ratio can be adjusted for different types of beer or to meet local preferences and requirements. The automatic tilting unit is compatible with all common jug or glass sizes (50 mm or more in inside diameter and 105 mm or less in outside diameter).

Perfect taste and temperature: An internal cooling system chills down the beer on its way from the keg through the machine. That means the draft beer can be served directly from ambient temperature kegs.

Cost and waste control: The beer is dispensed first, followed by foam which is poured from a separate spout. Thus, portion control can be very accurate, without spillage of beer and/or froth. Saving you up to 8 half-liter beers per 30 liter keg, the BeerMatic is a great tool for cost and waste control. Additionally, portion counter monitors the number of portions served.

Hygiene & Food Safety: As spillage is avoided entirely, the work space remains clean at all times. The dispenser's compartmentalized design is engineered to avoid contamination. The cleaning of the beer dispenser is a quick and easy process.

Perfect fit: With its compact design and small foot print this countertop dispenser fits into multiple environments. It can also be easily transported and installed for non-

AKCESORIA W KOMPLECIE

Taca ociekowa x 2, Kratka x 2, Platforma x 2

OBUDOWA

Przednie i boczne panele z tworzywa ABS,
plyta dolna ze stali ocynkowanej

- Two different types of beer can be served at one time
- Hands-free portion control
- Manual spring control
- Dispensing rate 4 jugs per minute. A portion counter monitors the number of portions served

• Designed for high-volume outlets. After initial freeze down 65 lt of beer can be served consecutively in 4 hours

Temperatura robocza (min./maks.): 5 °C / Temperatura otoczenia (maksymalna): 32 °C lowering the glass support base to the desired distance from each spout

- Folding or unfolding the spring-loaded base, beer can be served from each single tap into two pre-set sizes
- Compatible with jugs of 50 mm or more in inside diameter and 105 mm or less in outside diameter.

CERTYFIKATY



BEERMATIC DualTap DBF-AS65WE-EU



Dimensional drawing coming soon

SPECYFIKACJA TECHNICZNA

System chłodzenia	Zasilanie	Zabezpieczenie wyłącznika obwodu elektrycznego	Odprowadzanie ciepła (UT 32° C, WT 21° C)	Natężenie przepływu	Bezpośrednia wydajność po 45-minutowej przerwie	Bezpośrednia wydajność w ciągu 4 godzin po pierwszym 10-godzinnym okresie mrożeniu	Czas regeneracji
Chłodzona powietrzem	1/220 - 240V/50Hz	10 A	0,375 kW	0.034-0.049 l/s	10,2 l	65 l	45 m

SPECYFIKACJA WYSYŁKI

Szerokość (w opakowaniu)	Głębokość (w opakowaniu)	Wysokość (w opakowaniu)	Objętość (w opakowaniu)	Waga brutto	Szerokość	Głębokość	Wysokość	Waga netto
466 mm	795 mm	858 mm	0,318 m ³	56 kg	367 mm	674 mm	764 mm	50 kg