

SNOWFLAKE G II SUF-65DG-C-

C

1-Door Freezer Cabinet, HC



PRODUKTSERIE: SNOWFLAKE GII
ARTIKELNUMMER: 877010825

The Snowflake GII series is brought to you by Japanese and Danish engineering excellence, dedicated to simplifying the day-to-day work routines of kitchen staffs all around the world.

The technology behind the performance boost of Snowflake GII is the tropicalised cooling system enduring up to +40°C. Additionally, the cooling agent of the new generation of Snowflake is the eco-friendly refrigerant R290, a natural gas (HC) that enhances the performance and cuts down energy consumption significantly.

Both interior and exterior are built of anti-corrosion stainless steel AISI 304, which is among the best choices for hygienic and food safe cooking environments.

The Snowflake GII SUF-65BG is a 1 door freezer cabinet with a net internal volume of 398 Ltr.

SustainableThe refrigerant used in all Snowflake GII HC models is R290. This agent is a natural gas that enhances the performance of the refrigerated cabinet and has, compared to other refrigerants, a minimal ozone depletion potential. **Material**Both the interior and exterior of the refrigerated cabinet are built of stainless steel AISI 304, which is among the best choices for hygienic and food-safe cooking environments.**Energy Efficiency**The double insulated and extra wide door gaskets help to keep the cold air in the cabinet, which is an essential factor for device efficiency. The Ecodesign AEC Energy consumption is {{ energy_consumption_ecodesign_cabinets_counters }}. This Energy Efficiency Class of this unit is {{ energy_efficiency_class_cabinets_counters }}.With closed doors, this unit has an energy consumption of {{ energy_consumption_with_door_closed_cabinets_counters }} kWh.The Energy Efficiency Index EEI of this unit is {{ energy_efficiency_index_cabinets_counters }}. **Convenience and Ergonomics**The {{ modelname }} has an anti-tilt mechanism with molded liners for safer container and rooster handling. Additionally, the reversible doors offer maximum flexibility. The GN shelf size of the {{ modelname }} is {{ shelf_size_cabinets_counters }}. With sound levels of {{ sound_level_cabinets_counters }} dB(A) the {{ modelname }} adds to a comfortable work environment for your staff. **Food Safety**The removable gaskets

UTSIDA

Rostfritt stål AISI 304

INTERIÖR

Rostfritt stål AISI 304

Kylmedietyp: R290

Energieeffektivitetsklass

D



HOSHIZAKI

SNOWFLAKE G II SUF-65DG-C-C

TEKNISKA SPECIFIKATIONER

Temperaturområde	Hyllstorlek	Volym, brutto	Elektrisk anslutning	Klimaklass
-20/-10°C	2/1 GN djup	560 l	230V, 50Hz	5

FRAKTSPECIFIKATIONER

Bruttovikt	Bredd	Djup	Höjd	Nettovikt
140 kg	654 mm	840 mm	1 996 mm	140 kg



Måttritning kommer inom kort



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige order@hoshizaki.se
Hoshizaki UK uksales@hoshizaki.uk
Exportländer sales.ex@hoshizaki-europe.com
Andra länder sales.ex@hoshizaki-europe.com

www.hoshizaki.se