

SUR-135EG-R-C-U

2-Door Refrigerated Cabinet, HC



ARTIKELNUMMER: 878000904

The Snowflake GII series is brought to you by Japanese and Danish engineering excellence, dedicated to simplifying the day-to-day work routines of kitchen staffs all around the world.

The technology behind the performance boost of Snowflake GII is the tropicalised cooling system enduring up to +40°C. Additionally, the cooling agent of the new generation of Snowflake is the eco-friendly refrigerant R290, a natural gas (HC) that enhances the performance and cuts down energy consumption significantly.

Both interior and exterior are built of anti-corrosion stainless steel, which is among the best choices for hygienic and food safe cooking environments.

The Snowflake GII SUR-135DG-R-C U is a 2-door refrigerated cabinet with a net internal volume of 810 Ltr.

As a product that is designed and built to last, this refrigerated cabinet combines an innovative design concept, premium materials and clever extras:

- Minimum cool air lost: double insulated and extra wide door gaskets help to keep the cold air into the cabinet
- Both interior and exterior are built of stainless steel which is among the best choices for hygienic and food safe cooking environment
- Anti-tilt mechanism: moulded liners for safer container and rooster handling
- This and other thoughtful extras, such as the cleaning-free condenser, are designed to reduce kitchen cleaning times whilst storing foods protectively in the best possible way

The refrigerant used in all Snowflake GII HC models is R290. This agent is a natural gas which enhances the performance of the refrigerated counter and has, compared to other refrigerants, a minimal ozone depletion potential. R290 is one of the view refrigerants compliant with the called F-Gas Regulation, issued by the European Commission. This regulation aims to phase out HFCs (Hydrofluorocarbons) as of 2020 to make space for eco-friendlier alternatives and substances, such as HCs (Hydrocarbon) and find more information about the F-Gas Regulation.

UTSIDA

Nickelfritt rostfritt stål

INTERIÖR

Rostfritt

Kylmedietyp: R290 / Kylmedel: 0,085 kg / CO2-ekvivalent: 0,255 kg

Elförbrukning	Energieffektivitetsklass	Energieffektivitetsindex (EEI)
926 kWh	C	48,16 EEI



HOSHIZAKI

SUR-135EG-R-C-U

TEKNISKA SPECIFIKATIONER

Temperaturområde	Hyllstorlek	Volym, brutto	Netto nyttovolym	Elektrisk anslutning	Max anslutningseffekt	Klimaklass	Ljudnivå	Kylbehov (vid -10°C)
0/+10°C	2/1 GN djup	1 200 l	797 l	230V, 50Hz	250 kW	5	53 dB(A)	632 kW

FRAKTSPECIFIKATIONER

Bruttovikt	Bredd	Djup	Höjd	Nettovikt
192 kg	1 344 mm	830 mm	1 977 mm	192 kg



Måttritning kommer inom kort



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige order@hoshizaki.se
Hoshizaki UK uksales@hoshizaki.uk
Exportländer sales.ex@hoshizaki-europe.com
Andra länder sales.ex@hoshizaki-europe.com

www.hoshizaki.se