



HOSHIZAKI

SCR-225DG-LLRR-CRC-L1 4-Section Refrigerated Counter, HC

PRODUCT SERIE: SNOWFLAKE SCR
ARTIKELNUMMER: 879040820

The Snowflake GII series is brought to you by Japanese and Danish engineering excellence, dedicated to simplifying the day-to-day work routines of kitchen staffs all around the world.

The technology behind the performance boost of Snowflake GII is the tropicalised cooling system enduring up to +40°C. Additionally, the cooling agent of the new generation of Snowflake is the eco-friendly refrigerant R290, a natural gas (HC) that enhances the performance and cuts down energy consumption significantly.


Both interior and exterior are built of anti-corrosion stainless steel AISI 304, which is among the best choices for hygienic and food safe cooking environments.

The Snowflake GII SCR-225DG-LLRR-CRC-L1 is a 4-section refrigerated counter with a net internal volume of 343 Ltr.

As a product that is designed and built to last, this refrigerated counter combines an innovative design concept, premium materials and clever extras:

- Minimum cool air lost: double insulated and extra wide door gaskets help to keep the cold air into the cabinet
- Both interior and exterior are built of stainless steel AISI 304, which is among the best choices for hygienic and food safe cooking environments
- Anti-tilt mechanism: extra-long drawers with u-shaped, telescopic rails
- Multiple door-drawer combinations possible
- Removable gaskets make sure you can clean the device thoroughly
- This and other thoughtful extras, such as the cleaning-free condenser, are designed to reduce kitchen cleaning times whilst storing foods protectively in the best possible way

The refrigerant used in all Snowflake GII HC models is R290. This agent is a natural gas which enhances the performance of the refrigerated counter and has, compared to other refrigerants, a minimal ozone depletion potential.



**UITWENDIG
RvS AISI 304**

**INTERIEUR
RvS AISI 304**

Type koudemiddel: R290 / CO2-equivalent: 0,285 kg

Energie-efficiëntieklasse

C



HOSHIZAKI

SCR-225DG-LLRR-CRC-L1

TECHNISCHE SPECIFICATIES


Temperatuurbereik	Plankgrootte	Volume, bruto	Volume, netto	Klasse van het klimaat
-2/+8°C	1/1 GN diep	625 l	343 l	5

Voeding

230V, 50Hz

VERZENDSPECIFICATIES

Bruto gewicht	Breedte	Diepte	Hoogte inclusief poten (minimum)	Hoogte inclusief poten (maximum)	Netto gewicht
174 kg	2.246 mm	700 mm	830 mm	900 mm	174 kg



Maattekening volgt binnenkort



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige orderSE@hoshizaki.dk
Hoshizaki UK uksales@hoshizaki.uk
Exportlanden sales.ex@hoshizaki-europe.com
Andere landen sales.ex@hoshizaki-europe.com

www.hoshizaki.nl